



Conduit Fittings-PVC Coated T&B Catalog Number:

UPC Number: Status: Description: CB3/4-G 70450835954 Active

3/4 in. malleable iron gray pvc coated clamp-back spacer **Application**

	Provides space for air flow between conduit and mounting surface
General	
Trade Size (inches)	3/4
Material	Malleable Iron
Color	Gray
Technical Information	
Chemical Resistance Chart	Available on Website
Specifications	
Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website
Packaging	
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	11.25 lbs. per 100
Application Support	
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
Product Overview-Conduit Outlet Bodies	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General	Available on Website
Wiring	
NEC Table 8	Available on Website
Notes	
	Metric size designator (ANSI C80. 1-1994)
	Dimensions are of uncoated fittings
Certifications	
RoHS Compliance	Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com