


Clip-on™ Stamped Steel and Aluminum Covers and Separate Gaskets

For Form 7 Conduit Bodies



Type 170

Type 170 Stamped Steel and Aluminum Clip-on™ Cover

Use:

To cover conduit body opening.

Features:

- Centering tabs
- Easy installation
- Easy removal
- Nylon sealing washers

Material/Finish:

Stamped Steel/Zinc Pre-Galvanized
Stainless Steel Screws
Zinc Electroplated Clips

Optional Material:

Aluminum add suffix -SA as shown below

Third Party Certification:



UL Listed: E-18095

Suitable for wet locations when used with gaskets, Type GASK on Form 7 conduit bodies.



CSA Certified: 009795

Suitable for wet locations when used with gaskets, Type GASK on Form 7 conduit bodies.


Applicable Third Party Standards:

UL Standard: 514A

CSA Standard: C22.2 No. 18

Fed. Spec: A-A-50563

NEMA: FB-1, FB-2.10



Type GASK

Type GASK Solid Cover Gasket

Use:

To provide a worry-free, rain tight seal when used with Type 170 or 170F covers that have heavy-duty cover screw washers.

Material:

Closed-Cell Neoprene.
Temperature Rating: 212°F/100°C.


Note: UL/CSA not applicable.

Trade Size (inches)	Catalog Number Steel	Catalog Number Aluminum
1/2	170	170-SA
3/4	270	270-SA
1	370	370-SA
1 1/4	470	470-SA
1 1/2	570	570-SA
2	670	670-SA
2 1/2-3	870	870-SA
3 1/2-4	970	970-SA

Trade Size (inches)	Catalog Number
1/2	GASK571
3/4	GASK572
1	GASK573
1 1/4	GASK574
1 1/2	GASK575
2	GASK576
2 1/2-3	GASK578
3 1/2-4	GASK579

Clip-on™ Cast Iron and Cast Aluminum Covers and Separate Gaskets

For Form 7 Conduit Bodies



Type 170F

Type 170F Cast Gray Iron and Cast Aluminum Clip-on™ Cover

Use:

To cover conduit body opening.

Features:

- Centering tabs
- Easy installation
- Easy removal
- Nylon sealing washers

Material/Finish:

Gray Iron/Zinc Electroplated
Stainless Steel Screws
Zinc Electroplated Clips


Optional Finish


For additional corrosion protection, specify Hot Dip Galvanized. Add suffix "G" to Gray Iron catalog number. Contact your local representative for pricing and availability.

Optional Material

Cast Aluminum add suffix -SA as shown below


Third Party Certification:

 UL Listed: E-18095
Suitable for wet locations when used with gaskets, Type GASK on Form 7 conduit bodies.

 CSA Certified: 009795
Suitable for wet locations when used with gaskets, Type GASK on Form 7 conduit bodies.

Applicable Third Party Standards:

UL Standard: 514A
CSA Standard: C22.2 No. 18
Fed. Spec: A-A-50563
NEMA: FB-1, FB-2.10



Type GASK

Type GASK Solid Cover Gasket

Use:

To provide a worry-free, rain tight seal when used with Type 170 or 170F covers that have heavy-duty cover screw washers.

Material:

Closed-Cell Neoprene.
Temperature Rating: 212°F/100°C.

Note: UL/CSA not applicable.

Trade Size (inches)	Catalog Number Gray Iron	Catalog Number Cast Aluminum	Trade Size (inches)	Catalog Number
½	170F	170F-SA	½	GASK571
¾	270F	270F-SA	¾	GASK572
1	370F	370F-SA	1	GASK573
1¼	470F	470F-SA	1¼	GASK574
1½	570F	570F-SA	1½	GASK575
2	670F	670F-SA	2	GASK576
2½-3	870F	870F-SA	2½-3	GASK578
3½-4	970F	970F-SA	3½-4	GASK579