







PCSB4-6-6Y

Multi-Tap connector, double-sided, clear insulation, 6 ports, #4 - #14 STR, #10 - #14 SOL.

[Specs](#)
 [Packaging Details](#)
 [Documents](#)
 [★ Add to Favorites](#)
 [🛒 Add to BOM](#)

Material	Aluminum / Clear PVC
Conductor Material	Copper and Aluminum
Product Type	Multi-Tap Mechanical Connectors, Double Sided
Copper and Aluminum Conductor Size Range	#4 - #14 AWG STR #10 - #14 AWG SOL
No. of Ports	6
Stud Hole Size In. (mm)	—
Stud Hole Spacing In. (mm)	—
Stud Hole Spacing In. (mm)	—
Height 1 In. (mm)	—
Height 2 In. (mm)	—
Height In (mm)	1.25 (31.8)
Hex Key Size (In.)	1/8
Length In (mm)	3.35 (85.1)
Mounting Hole Spacing In. (mm)	—
NEMA Hole Spacing	—
Width In (mm)	1.50 (38.1)
CSA Certified	C22.2 No. 65-13
Max. Voltage Rating	—
Tin-Plating Meets ASTM B545-97, Class C	320μ-in (8 μm)
UL Listed	486A-486B File #E52164
UL Temperature Rating	—
UL and CSA Temperature Rating	90°C
UL and CSA Voltage Rating	600V
Insulation	Clear PVC
Part Number Series	PCSB
Part Number Series	PCSB

Includes	Each port pre-filled with oxide inhibiting joint compound
Part Features	Each port pre-filled with oxide inhibiting joint compound seals out air and moisture to deter surface oxidation.
Sub Brand	Pan-Lug
RoHS Compliancy Status	Compliant
Min. Order Qty.	1

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)