

EdgeConnect™, Straight Blade  
Devices, Plug,  
Industrial/Commercial Grade, 2-  
Pole 3-Wire Grounding, 20A 125V,  
5-20P, Black and White

By Hubbell Wiring Device-Kellems  
Catalog # [HBL5366CST](#)



EdgeConnect™, Straight Blade Devices, Plug,  
Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 20A  
125V, 5-20P, Black and White

Application

Extra Heavy Duty Industrial/Commercial Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	HBL5366CST
Color	Black and White
Cord Range	0.230"-0.720"(5.8-18.3)
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	1
Insulation	Insulated Body
Item Type	Insulgrip® Plug
Material	Nylon
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum without Impact -40 °C
Series	EdgeConnect™
Size	3.28 in x 1.41 in x 1.09 in
Specifications	Blade Holder - Nylon, Retainer - Polycarbonate, Cover - Nylon, Cord Clamp - Nylon, Contact

Style

Temperature Rating

Type

UPC

Dimensions

Display Size

Weight

Electrical Ratings

Connectivity

Current / Amperage Rating

Dielectric Strength

Phase

Voltage Rating

Conductor Related

Conductor Range

Cord Type

Number Of Wires

Number of Conductors

Wire Size

Certifications And Compliance

Industry Standard(s)

Nema Rating

Blades - Copper Alloy, Spring - Stainless Steel, Plunger - Nylon, Drive/Assembly/Cord Clamp Screws - Steel  
Standard  
Maximum continuous 75°C; minimum -40°C (w/o impact)  
Plugs  
783585964812

Standard Sized Product  
0.2 lb

Spring Termination  
20 A  
Withstands 2,000V minimum  
Single Phase  
125 V

#14 AWG to #10 AWG  
All Listed Portables  
3-Wire  
3-Wire Grounding  
#14 AWG to #10 AWG

- CSA Certified to C22.2 No. 42 File 280
  - Fed. Spec. W-C596G
  - NEMA® WD-6 Compliant
  - UL Listed to UL498 File E1706
- 5-20P

Logistics

Carton Quantity 10

Product Assets

Catalog Page - WDK A-38 Catalog Page  
Catalogs - WDK Catalog Full 2024

Installation Manuals - PD3057  
Literature - EdgeConnect™ Technology FAQ  
Literature - EdgeConnect™ Technology  
Literature - EdgeConnect™ Termination vs Standard Push Wire  
Sales Drawings - M14563  
Specifications - HBL5366CST  
Warranty - Industrial & Commercial Products



A Hubbell brand