


T12 Medium Bipin (1-1/2" diameter)



U-Shaped T12 (1-1/2" diameter) 6" leg spacing

T12 RAPID START FLUORESCENT LAMPS

4-Foot SUPERSAVER® Rapid Start Lamps; Vivid Color: High CRI for color critical applications

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	Average Rated Life @12hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
34	T12	48	47.78	Medium Bipin	24588	F34CW/SS (F40CW/SS)	30	20000	28800	4100	87	1925 (1655)	☀️, 3, 8, 12, 13, 17
					22425	F34T12/941/SS/ECO	30	20000	28800	4100	90	2650 (2450)	☀️, ⭐️, 3, 8, 12, 13, 17
					24599	F34/DX/SS (F40/DX/SS)	30	20000	28800	6500	88	1930 (1565)	☀️, 3, 8, 12, 13, 17

4-Foot Standard Rapid Start Lamps; Vivid Color: High CRI for color critical applications

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	Average Rated Life @12hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
40	T12	48	47.78	Medium Bipin	23505	F40/WX	30	20000	28800	3500	87	2100 (1805)	☀️, 3, 12, 13, 17, 23
					24441	F40CWX	30	20000	28800	4100	87	2150 (1850)	☀️, 3, 12, 13, 17, 23
					24683	F40DSGN50	30	20000	28800	5000	90	2200 (1890)	☀️, 3, 12, 13, 17, 23
					24477	F40/DX	30	20000	28800	6500	88	2180 (1770)	☀️, 3, 12, 13, 17, 23

3-Foot SUPERSAVER Rapid Start Lamps

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
25	T12	36	35.78	Medium Bipin	23472	F25T12/CW/RS/SS (F30T12CWRSSS)	30	18000	4200	60	1925 (1635)	☀️, 3, 7, 12, 13, 17

3-Foot Standard Rapid Start Lamps

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
30	T12	36	35.78	Medium Bipin	23474	F30T12/D830/RS	30	18000	3000	80	2290 (2060)	☀️, 3, 7, 12, 13, 17
					23482	F30T12/WW/RS	30	18000	3000	52	2275 (1935)	☀️, 3, 7, 12, 13, 17
					23484	F30T12/D35/RS	30	18000	3500	70	2250 (1980)	☀️, 3, 7, 12, 13, 17
					23476	F30T12/CW/RS	30	18000	4200	60	2200 (1870)	☀️, 3, 7, 12, 13, 17
					23478	F30T12/D/RS	30	18000	6500	76	1900 (1615)	☀️, 3, 7, 12, 13, 17

CURVALUME® T12 SUPERSAVER® & CURVALUME Standard Rapid Start Lamps – U-Shaped 6" Leg Spacing

Vivid Color: High CRI for color critical applications

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
34	T12	22.5	22.6	Medium Bipin	24965	FB34T12/930/6/SS/ECO	12	18000	3000	90	2600 (2340)	☀️, 3, 8, 12, 13, 17
					24308	FB34T12/941/6/SS/ECO/UPC	12	20000	4100	90	2650 (2385)	☀️, 3, 8, 12, 13, 17
40	T12	22.5	22.6	Medium Bipin	24004	FB40/CWX/6	12	18000	4100	87	2100 (1785)	☀️, 3, 8, 12, 13, 17