

Rittal – The System.

Faster – better – everywhere.

LED compact system light – SZ 4140.820

Date : May 31, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



LED compact system light – SZ 4140.820

created: 31.05.2017 build on www.rittal.com/us-en



Product description

Benefits:	Max. EMC capacity. Protected with the safety extra-low voltage range Economical energy use. Low-maintenance with the use of LEDs. May be connected to a door-operated switch.
Function principle:	Integral through-wiring. Universal attachment options. Vertically hinged light cone.
Material:	Light body: Extruded aluminum Light cover: Polycarbonate (halogen-free) Light ends: PC-ABS
Color:	Similar to RAL 7035
Protection category IP to IEC 60 529:	IP 20
Supply includes:	LED compact system light Light (bulb) Light cover Assembly components
Note:	Only intended for use in enclosures and closed housings When using on customer-supplied power packs, it is important to obtain the requisite approvals depending on the application The maximum rated current when installing luminaires is 2 A

Product features

Dimensions: Height: 32.8 mm (1.3 ")

Width: 330 mm (13 ")
Depth: 20.64 mm (0.81 ")

Rated operating voltage:	24 V (DC) Voltage tolerance: ± 10 %
Installation options:	TS horizontal profile from roof frames: direct TS, SE vertical profile, direct SE profiles to the front and rear of roof frames: direct SE profiles to the side of roof frames: direct AE, CM, TP: with magnetic fastener AE: with rail for interior installation
Mounting dimensions:	Mounting distance – clip/magnet: 275 mm (11 ") Mounting distance – screw attachment: 350 mm (14 ")
Rated current:	with DC (max.): 0.08 A Note: The maximum rated current when installing luminaires is 2 A
Equipment (electrical):	Light (bulb): LEDs, cool white Switch (type): Integral, on/off/door-operated switch mode
Rated insulation voltage:	Depending on the power supply
Rated impulse withstand voltage, phase to earth:	Depending on the power supply
Rated impulse withstand voltage, phase to phase:	Depending on the power supply
Number of LEDs:	20
Protection category:	III (SELV)
Connection options:	Power supply through connector Door-operated switch Through-wiring (configuration of row of luminaires)
Light – installation type:	Screw fastening Clip fastening Magnetic fastener (accessories)
Light cover:	yes
Light cone adjustment:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.3 kg (0.7 lb.)
EAN:	4028177630130

Customs tariff number:	94054099
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description (long):	SZ LED system light, WHD: 330x33x21 mm, 24 V DC, Integral on/off/door-operated switch mode
Approvals	
Certificates:	EAC
Declarations:	Declaration of conformity

2017 © Rittal Corporation