

## RAPID START LAMPS

### High Output (800mA) Standard Rapid Start Lamps

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life		CCT (K)	CRI	Approx Lumens Initial (Mean) 25°C/77°F	Notes
								3 Hours per start	12hrs				
85	T12	72	69.91	RecessedDC	25098	F72T12/D830/HO	15	12000		3000	80	6750 (6210)	1,3, 12,13,17
					25177	F72T12/WW/HO	15	12000		3000	52	6400 (5185)	3,12, 13,17
					27249	F72T12/D35/HO	15	12000		3500	70	6650 (5985)	3,12, 13,17
					25281	F72T12/D835/HO	15	12000		3500	80	6750 (6210)	3,12, 13,17
					25176	F72T12/CW/HO	15	12000		4200	60	6250 (5065)	3,12, 13,17
					25171	F72T12/CW/HO/ECO	15	12000		4200	60	6250 (5065)	1,3, 12,13,17
					25190	F72T12/DSGN50/HO	15	12000		5000	90	4600 (3725)	1,3, 12,13,17
					25189	F72T12/D/HO	15	12000		6500	76	5550 (4495)	1,3, 12,13,17
100	T12	84	81.91	RecessedDC	25384	F84T12/CW/HO	15	12000		4200	60	7550 (6115)	3,12, 13,17
					25385	F84T12/D/HO	15	12000		6500	76	6700 (5425)	3,12, 13,17
110	T12	96	93.91	RecessedDC	25149	F96T12/D30/HO	15	12000	18800	3000	70	9050 (8145)	1,3, 12,13,17,36
					25152	F96T12/D830/HO	15	12000	18800	3000	80	9400 (8650)	1,3, 12,13,17,36
					25165	F96T12/D35/HO	15	12000	18800	3500	70	9050 (8145)	1,3, 12,13,17,36
					25166	F96T12/D835/HO	15	12000	18800	3500	80	9400 (8650)	1,3, 12,13,17,36
					25155	F96T12/D841/HO	15	12000	18800	4100	80	9400 (8650)	1,3, 12,13,17,36
					25184	F96T12/D41/HO	15	12000	18800	4100	70	9050 (8145)	1,3, 12,13,17,36
					25164	F96T12/DSGN50/HO	15	12000	18800	5000	90	6450 (5225)	3, 12,13,17
					25185	F96T12/D865/HO	15	12000	18800	6500	80	8800 (7920)	1,3, 12,13,17,36

\*means this bulb meets Federal minimum efficiency standards