



BURNDY Catalog Number	BIPC5004/0
UPC Number	781810128756
Description	500-4/0KCMIL INSL PRCCON
Status	Active

Web Use  
BURNDY Product Line

Dimensional	
Width (in)	2.62
Length (in)	1.80
Bolt Size (in)	0.380
Height (in)	3.25
Electrical	
Max Voltage Rating	600
General	
Product Description	Insulation Piercing Connector, 350-500 kcmil (Run), 4-4/0 AWG (Tap), 600 V
Conductor(s)	
Aluminum Run Size (Range)	350 kcmil-500 kcmil
Copper Tap Range	4 AWG-4/0 AWG
Copper Stranded Run (Range)	350 kcmil-500 kcmil
Aluminum Tap Size (Range)	4 AWG-4/0 AWG
Physical	
Installation Torque	400
Type of Plating	Unplated
Plated (Yes or No)	N
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
Rated for Direct Burial	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA  
47, industrial Park Drive  
Manchester NH03109

BURNDY Technical Services  
47, industrial Park Drive  
Manchester NH03109

Hours: 8.00 AM - 5.00 PM  
Monday - Friday  
Phone: 000-346-4175