


T5 | T8 Wet Location 2' | 4'

Construction

Tethered Ballast Tray **Stainless Steel Mounting Clips Composite Housing** Poured Gasket IP67 Rated NSF Rated





Options & Accessories



Poured Gasket

Ordering Format





Tethered Ballast Tray



Stainless Steel Mounting Clips




Wet Location Motion Sensor*

example: IFW 2 U 3C 4 54 EP5 FIXTURE LENGTH WATTAGE BALLAST 4 = 4 Feet 32 = 32W T8 EI8 = T8 Electronic Instant Start 8 = 8 Feet 54 = 54W T5HO EP8 = T8 Electronic Program Start EP5 = T5HO Electronic Program Start PRODUCT SERIES LAMPS VOLTAGE OPTIONS IFW = Wet Listed 2 U = Universal 3C = 3' Cord (No Plug) Linear Fluorescent (120-277) F = Inline Fusing N = No Lamps83 = 835 Lamps 85 = 850 Lamps

Ambient Temperatures

PART #	DESCRIPTION	CEILING MOUNT
IFW4254UEP5	4 ft., 2 Lamp, 54w T5HO	104°F/40°C
IFW4232UEI8	4 ft., 2 Lamp, 32w T8	86°F/30°C
IFW8254UEP5	8 ft., 4 Lamp, 54w T5HO	104°F/40°C
IFW8232UEI8	8 ft., 4 Lamp, 32w T8	95°F/35°C



L = Stainless Steel Latches M = Motion Sensor*

