## Thomas&Betts



## Conduit Fittings-PVC Coated T&B Catalog Number:

UPC Number: Status: Description: ST3/490-G 70450840767 Active

3/4 in. Dark Gray PVC Coated 90 degree Liquidtight Connector. Fitting material-Steel. **Features** 

	A minimum of .040 in. (40 mil) PVC coating is bond-
	ed to the exterior.
	Double coated with a nominal .002 in. (2 mil) blue
	urethane on both the interior and exterior, before
	PVC coating is applied.
	Pressure-sealing sleeves are designed to protect
	the connection.
	PVC coated connectors are available in straight, 45
	degree and 90 degree configurations
	Ocal uses T&B Industrial Liquidtight fittings to in-
	sure quality installations.
Application	
	To positively bond conduit to box or enclosure
General	To positively bond conduit to box of enclosure
General	
Custom_Finish	lt_34_90
Trade Size (inches)	3/4
Material	Steel
Finish	PVC Coated
Color	Dark Gray
Dimension Information	,
Pipe Size (Metric Size Designator*)	21
Dimension A (inches)	1 21/32
Dimension B (inches)	1 3/4
Dimension C (inches)	9/16
Technical Information	
Chemical Resistance Chart	Available on Website
Specifications	
Ocal Specification Cuide 1005 Master	Available on Website
Ocal Specification Guide-1995 Master Format-PDF	Available of Website
Ocal Specification Guide-1995 Master	Available on Website
Format-DOC	Available on website
Ocal Specification Guide-2004 Master	Available on Website
Format-PDF	Available on website
Ocal Specification Guide-2004 Master	Available on Website
Format-DOC	
Packaging	
Packago in Unito	50
Package in Units T&B Sold in UOM	Each
	0.44 lbs. Each
T&B Weight Per UOM	0.44 IDS. EACH
Application Support	
Ocal Specifications	Available on Website
· .	



Recommended Installation Procedures	Available on Website
Product Overview-Conduit Outlet Bodies	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website
Notes	
	Dimensional values are of uncoated liquidtight fit- tings.
	Metric size designator (ANSI C80. 1-1994)

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com