



# Contractor Grade Duct Tape

## 2979

Technical Data

August 2013

**Product Description** 3M™ Contractor Grade Duct Tape 2979 is a utility grade, conformable cloth duct tape made with polyethylene film over cloth scrim and high adhesion synthetic rubber adhesive. A good choice for protecting, bundling, attaching, poly hanging, holding, and marking.

### Product Construction

Backing	Adhesive	Color	Standard Roll Length	Standard Width
Polyethylene film over cloth scrim	Synthetic rubber	Silver	60 yds (54.8 m)	1.88" (48 mm) 2.83" (72 mm)

### Typical Physical Properties

**Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

	ASTM Test Method
Adhesion to Steel:	79 oz./in. width (86 N/100 mm) D-3330
Tensile Strength:	24 lbs./in. width (420 N/100 mm) D-3759
Elongation at Break:	21% D-3759
Tape Thickness:	7.4 mils (0.29 mm) D-3652
Temperature Use Range:	Up to 200°F (93°C)

### Features

- Aggressive synthetic rubber adhesive provides instant adhesion to a wide variety of surfaces, including concrete, wood, and metal.
- Woven cloth scrim tears straight in both directions.
- Thick yet stretchable backing easily conforms to irregular surfaces.

### Application Ideas

- Hanging poly-drapes
- Trip hazard mitigation
- Wire pulling
- Bundling, attaching, marking, identifying

### Storage

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

### Shelf Life

To obtain best performance, use this product within 18 months from date of manufacture.

# 3M™ Contractor Grade Duct Tape

2979

---

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

## Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**ISO 9001**

This Industrial Adhesives and Tapes Division product was manufactured under a quality system registered to ISO 9001 standards.



### Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
www.3M.com/industrial



*Recycled Paper*  
40% pre-consumer  
10% post-consumer

3M is a trademark of 3M Company.  
Printed in U.S.A.  
©3M 2013