Product Name: 172 Standard Weld Metal Revision Date: 19 October 2015 (rev C) Page 1 of 8



SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: 172 Standard Weld Metal

Product Description: Gray / silver granular metal

Intended Use: Welding metal

COMPANY IDENTIFICATION

Supplier:

BURNDY LLC 47 East Industrial Park Drive Manchester, NH 03109 USA

24 Hour Emergency (INFOTRAC)

Burndy Informational Number

HAZARDS IDENTIFICATION

(603) 647-5000

(800) 535-5053 (US and Canada) (352) 323-3500 (International)

CLASSIFICATION

SECTION 2

Health	Environmental	Physical
 Acute Toxicity - Oral, Category 4 Skin Irritation - Category 3 Eye Irritation - Category 2B 	 Acute toxicity - Category 1 	•Flammable Solids - Category 1

LABELLING

Symbols:	¥2
Flame Health Hazard	Environmental
	Hazard
Signal Word: Warning	
Hazard Statements	Precautionary Statements
 •H 302: Harmful if swallowed •H 411: Toxic to aquatic life and may cause long lasting harmful effects •H 320: Causes eye irritation •H 228: Flammable Solid •H315: Causes skin irritation 	 P 273: Avoid release to the environment P 261: Avoid breathing dust/fume/gas/mist/vapors/spray P 264: Wash thoroughly after handling P 280: Wear protective gloves/clothing



Product Name:172 Standard Weld MetalRevision Date:19 October 2015 (rev C)Page 2 of 8

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Substance(s) or Complex Substance(s)

Name	Common Name/Synonym	CAS #	Percentage	Impurities	Risk Phrases
Copper	-	7440-50-8	50-70	None Known	
Cuprous oxide	-	1317-39-1	20-40	None Known	
Aluminium (fume or dust)	-	7429-90-5	7-13	None Known	
Calcium flouride	-	7789-75-5	1-5	None Known	Refer Section
Tin	-	7440-31-5	1-5	None Known	15
Iron oxide, black	-	1317-61-9	1-5	None Known	
Calcium Silicon	-	Mixture	1-5	None Known	

* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume. The exposure limits of this product, when allowed to enter the environment as dust particulate, are covered under the rules of 29 CFR 1910.1000, Table Z -3, "All inert or nuisance dusts, whether mineral, inorganic or organic."

SECTION 4

FIRST AID MEASURES

ROUTES OF ENTRY: Inhalation, Ingestion, Contact

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation: Remove affected person to fresh air; if symptoms persist seek medical attention.

<u>Eye Contact:</u> Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

<u>Skin Contact</u>: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

<u>Ingestion</u>: Give two glasses of water for dilution; induce vomiting as directed by medical personnel; never give anything by mouth to an unconscious person; seek medical attention.

SECTION 5

FIRE FIGHTING MEASURES

GENERAL HAZARDS

Products of combustion include metal oxides and metal dust.

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use carbon dioxide, water, water fog, dry chemical, chemical foam, dry sand.

Inappropriate Extinguishing Media: None known



Product Name: 172 Standard Weld Metal Revision Date: 19 October 2015 (rev C) Page 3 of 8

FIRE FIGHTING PROCEDURES

Fire Fighting Instructions: Firefighters must wear full face piece self - contained breathing apparatus in positive pressure mode.

Unusual Fire Hazards / Combustion Products: BURNDY Weld copper base welding/joining materials are exothermic mixtures, which when reacted, produce hot molten materials with temperatures in excess of 4000° F and a localized release of smoke. The materials are not explosive, ignition temperatures are in excess of 850° F for starting material and 1750° F for base material. They are not shock sensitive, nor are they subject to spontaneous ignition. Should the material be accidentally ignited, the immediate and direct application of large volumes of water will effectively retard the spread of fire and control it. Large amounts of dense, dusty smoke will be liberated during an accidental fire.

Smoke, oxides of carbon; fumes of copper and aluminum. Small amounts of fluoride fume or hydrofluoric acid fume may be released under ignition.

ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Confine and segregate product for reuse; place material into approved containers for disposal; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313, 40 CFR 372 for reporting requirements. Do not discharge into lakes, ponds, streams or public waters.

SECTION 7

SECTION 6

HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Storage of BURNDYWeld Exothermic materials should be in a clean dry area and restricted to access by authorized personnel only. Do not subject to rough handling or physical damage, nor excessive vibration. Store in accordance with "This Side Up" labels. Protect from weather and moisture. DO NOT USE PRODUCTS THAT HAVE BEEN EXPOSED TO MOISTURE. Before using BURNDYWeld Exothermic Process, personnel should be trained by a BURNDYWeld representative. Read and understand the instruction sheet packaged with the mold, and observe all general and safety instructions.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Component name	CAS #	TWA/STEL	NIOSH	ACGIH	Note
Copper	7440-50-8	TWA	0.1 mg/m ³	0.2 mg/m ³	-
Cuprous oxide	1317-39-1	TWA	1 mg/m ³		-
Aluminium (fume or dust)	7429-90-5	TWA	10 mg/m ³	10 mg/m ³	-
Calcium fluoride	7789-75-5	TWA	Not Established	Not established	-
Tin	7440-31-5	TWA	2 mg/m ³	2 mg/m ³	0.2 mg/m ³ (STEL)
Iron oxide, black	1317-61-9	TWA	10 mg/m ³	10 mg/m ³	-
Calcium Silicon	Mixture	TWA	Not established	Not established	-



Product Name: 172 Standard Weld Metal Revision Date: 19 October 2015 (rev C) Page 4 of 8

PERSONAL PROTECTIVE EQUIPMENT

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: NIOSH approved respirator designed to remove airborne particulate present in excess of maximum allowable concentrations due to secondary operations such as mixing, spraying, sanding, buffing, etc. Refer to 29 CFR 1910.134 or European Standard EN 149 for regulations.

Hand Protection: Neoprene or rubber gloves may be used when handling product.

Eye Protection: Protective eyeglasses or chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

Other protective clothing or equipment: Safety eyebath nearby.

Work or Hygienic Practices: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

SECTION 9

PHYSICAL/CHEMICAL PROPERTIES

GENERAL INFORMATION

Physical State: Solid Color: Gray/ Silver Odor: Characteristic odor Odor Threshold: Not Available

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Appearance: Gray/ Silver granules pH: Not Applicable Viscosity: Not Applicable Freezing Point: Not Available **Boiling Point:** Not Applicable Flash Point: Not Applicable Evaporation Rate: Not Applicable Lower Flammability Limit: Not Applicable Upper Flammability Limit: Not Applicable Vapor Pressure: Not Applicable Vapor Density (Air=1): Not Applicable Specific Gravity (Water = 1): Approximately 6.0 Solubility in Water: Insoluble Coefficient of Water/Oil Distribution: Not Available Auto-ignition Temperature: > 1750 °F (> 955 °C) Percent Volatile, wt. %: Not Available VOC content, wt. %: Not Available

SECTION 10

STABILITY AND REACTIVITY

STABILITY: Product is stable under normal conditions.

CONDITIONS TO AVOID: Avoid generating airborne dust, avoid moisture.

INCOMPATIBLE MATERIALS: Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition will not occur if handled and stored properly. In case of fire, smoke, oxides of carbon; fumes of copper and aluminum. Small amounts of fluoride fume or hydrofluoric acid fume may be released under ignition.



Product Name:172 Standard Weld MetalRevision Date:19 October 2015 (rev C)Page 5 of 819

POSSIBILITY OF HAZARDOUS REACTIONS: HAZARDOUS POLYMERIZATION will not occur

SECTION 11

TOXICOLOGICAL INFORMATION

ACUTE TOXICITY VALUES

Ingredient		
	(Specify species and Route)	
Copper	LD ₅₀ : Not determined	-
	LC ₅₀ : Not determined	
Cuprous oxide	LD ₅₀ : 470 mg / kg Oral-rat	-
	LC_{50} : 11 µg / m3 / 24H Inhalation - rat	
Aluminium (fume or dust)	LD ₅₀ : Not established	-
	LC ₅₀ : Not established	
Calcium flouride	LD ₅₀ : 4250 mg/kg Oral- rat	-
	LC ₅₀ : Not established	
Tin	LD ₅₀ : Not established	-
	LC ₅₀ : Not established	
Iron oxide, black	LD ₅₀ : Not established	-
	LC ₅₀ : Not established	
Calcium Silicon	LD ₅₀ : Not established	-
	LC ₅₀ : Not established	

ACUTE EFFECTS

Eye Contact: Contact with eyes may cause irritation.

Skin Contact: None expected, however, prolonged contact may cause irritation.

Inhalation: Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract. Contains substances which are considered nuisance dusts which require a NIOSH approved respirator when airborne particulate exceeds maximum allowable limit.

Ingestion: May cause gastric distress, stomach pains, vomiting and diarrhea.

Carcinogenicity: IARC: NO NTP: NO OSHA Regulated: NO

SECTION 12 ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. Copper Oxide in the mixture is classified as a Marine Pollutant.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable Local, State and Federal laws and regulations, and material characteristics at time of disposal.

WASTE DISPOSAL METHOD:

According to the European Waste Catalogue, waste codes are application specific and should be assigned by the user based on the application for which the product is used. Dispose of in accordance with Local, State, and Federal Regulations. Do not flush to sanitary sewer or waterway. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.



Product Name: 172 Standard Weld Metal 19 October 2015 (rev C) Revision Date: Page 6 of 8

SECTION 14	14 TRANSPORTATION						
Regulatory Information	UN Number	Proper Shipping Name	Hazard Class	Packing Group	Label (s)	RQ	Additional Information
US DOT	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper Oxide)	9	III			Only regulated for transportation as a hazardous substance
TDG	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper Oxide)	9	111			
					UN3077		May be offered as a Limited Quantity (See TDG Schedule 1)
ADR	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper Oxide)	9	111	<u>•</u>		
							May be offered as a Limited Quantity (See ADR Table A)
ΙΑΤΑ	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper Oxide)	9	111			
					Y		May be offered as a Limited Quantity (See IATA PI Y911)
IMDG	UN3077	Environmentally hazardous substance, solid, n.o.s. (Copper Oxide)	9	111			Copper oxide is a severe marine pollutant



Product Name: 172 Standard Weld Metal Revision Date: 19 October 2015 (rev C) Page 7 of 8

SECTION 15

REGULATORY INFORMATION

TSCA (USA - Toxic Substance Control Act

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (USA - Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories Immediate health

313 Reportable Ingredients:

(a) Indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To- Know Act of 1986 and of 40 CFR 372

CERCLA (USA - Comprehensive Response Compensation and Liability Act)

(b) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, if < 4 μ diameter, according to 40 CFR 302

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: Not controlled

IDL (Canadian Ingredient Disclosure List)

Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 3.

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 3 unless otherwise indicated.

EUROPEAN INVENTORY OF EXISTING CHEMICALS (EINECS):

Chemical Name	CAS Number	EINECS Number	R-Phrase
Cuprous oxide	1317-39-1	215-270-7	R-Not Classified
Copper	7440-50-8	231-159-6	R-Not Classified
Aluminum (fume or dust)	7429-90-5	231-072-3	R-15, R-17
Calcium Fluoride	7789-75-5	232-188-7	R-20/22, R-36/37/38
Tin	7440-31-5	231-141-8	R-11, R-36/37/38
Iron oxide, black	1317-61-9	Not Assigned	R-36/37/38
Calcium Silicon	Mixture	Not Assigned	Not classified

Product Name: 172 Standard Weld Metal Revision Date: 19 October 2015 (rev C) Page 8 of 8



WGK Water Quality Rating: 1 VbK Index:

EU RISK (R) AND SAFETY (S) PHRASES:

- R11: Highly flammable
- R 15: Contact with water liberates extremely flammable gases
- R 17: Spontaneously flammable in air
- R 20/22: Harmful by inhalation and if swallowed
- R 36/37/38: Irritating to the eyes, respiratory system and skin
- S 22: Do not breathe the dust.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

SECTION 16 OTHER INFORMATION

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) RATINGS:

Health - 1 Flammability - 0 Physical Hazard - 0 PPE - E

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Date	Description	Sections Affected
2/13/08	Rev 1	
6/2/11	Rev 2	Sec 11, Transportation
8/1/11	Rev 3	All
11/6/12	Rev 4	Sections 2, 3, 4, 5, 6, 7, 9, 10, 11 & 15
3/19/13	Rev 5	Sec 11
9/16/14	Rev 6	2-16
10/30/14	Rev 7	-
10/19/15	Rev C	All

This SDS provides a good faith representation of information believed to be accurate as of the last revision date. This document does not create any express or implied product warranties. Since conditions of use are beyond the control of Burndy LLC, all risks associated with product use are assumed by the user.