


EMA108-10
G3 MANAGED

FUNCTIONALITY CURRENT, POWER, AND ENERGY METERING FOR INPUT, BRANCH AND OUTLET; OUTLET SWITCHING	INPUT NEMA L5-30P 10FT 10AWG / 3C POWERCORD	OUTPUT (24) NEMA 5-20R	OPERATING TEMPERATURE 32° TO 140° F 0° TO 60° C
MECHANICAL 66.50" (1689mm) LENGTH 2.05" (52mm) WIDTH 2.56" (65mm) DEPTH ALUMINUM CHASSIS, BLACK	INPUT RATING 100-127V~ W+N+PE 24 A 50/60 Hz	OUTPUT RATING 100-127V~ 16A MAX PER OUTLET 16A MAX PER SECTION 24A MAX TOTAL	CERTIFICATIONS 
CIRCUIT BREAKERS (2) 20A 1-POLE LISTED	FILTER AND SPIKE/SURGE NONE	ACCESSORIES INCLUDED SPK012 - INSTALLATION INCLUDED SPK013 - NETWORK OPTIONAL EMP001 - ENVIRONMENTAL PROBE	CONFIGURATION EMA6MG15EMH88AC

TITLE	ePDU G3 SPECIFICATION EMA108-10	DRAW	Spock Liu	2014-06-24
DWG NO.	B9001-221490-00P	DESIGN	Spock Liu	2014-06-24
MATERIAL		CHECKED	Deng Dai	2014-06-24
COATING		SAFETY	Merry Sun	2014-06-24
UNITS	in[mm]	APPROVED	Vicky Shen	2014-06-24
SHEET	1/1	