

T&B Conduit Fittings

Rigid and Intermediate Metal Conduit Fittings




Steel or malleable iron or aluminum.

CHASE® Nipples

SII.orM.I.	Cat.No.		Size	Dimensions (in.)	
		Alum.		A	B
841 TB		—	H"	5%	5fe
842TB		842ALTB†	W	1V4	%
843TB		843ALTB	34"	1%	%
844		844AL†	r	1%	%
845		845AL†	W	2	25/32
846		846AL	1½"	23/8	17/8
847		847AL	2"	2%	%
848		848AL	2W	39/16	17/16
849		849AL	3"	43/8	1¼
850		850AL	3½"	5V4	15%
851		B51AL	4"	5	15%
853		853AL	5"	6½	15%
854		854AL	6"	7V4	1H

† Not UL Listed
Available with DURA-PLATE® Finish.
U.L. File No. E-23018
CSA File No. 2884



Steel or malleable

CHASE® Nipples -Nylon Insulated

Cat. No.	Size	Dimensions (in.)		
		A	B	C
1942	½"	13/32	7/8	9/16
1943	¾"	1%	1fa	%
1944	r	11/16	21/32	%
1945	1W	21/32	5fe	1>fe
1946	1½"	2H	39/16	1732
1947	2"	219/16	%	1%
1948	2½"	39/16	1)%	17/16
1949	3"	43/8	13/16	1%
1950	3½"	51/8	1718	123/32
1951	4"	5V*	15%	1%
1953	5"	6%	15%	Wfe
1954	6"	7*	1J*	1%

U.L. File No. E-23018
CSA File No. 2884

