

BX, Flex Connectors

90° - Squeeze Type - Zinc



Features

- Squeeze type

Applications


- Indoor use only
- In a dry location, use to connect flexible metallic conduit, AC and MC cable to a steel outlet box, or other metal enclosure
- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" - 3/4" steel and aluminum armored cable, steel and aluminum interlocked metal clad cable, flexible cord, and 1" - 4" flexible metallic conduit

Standard Material

- Zinc die cast
- Zinc plated steel strap

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
100	10340	3/8" 1/2" KO	50	500	45	1.74	.43 - .72	.37	2
101	10350	1/2"	25	250	35	2.11	.64 - 1.03	.40	2
102	10360	3/4"	10	100	20	2.40	.76 - 1.15	.40	2
103	10370	1"	5	50	19	2.87	1.09 - 1.73	.54	2
104	10380	1-1/4"	10	40	20	4	1.34 - 1.97	.64	2
105	10390	1-1/2"	---	5	5	6	1.65 - 2.61	.75	2
106	10400	2"	---	5	6	6	1.54 - 2.54	.74	2
107	10410	2-1/2"	---	5	18	7.187	2.45 - 2.98	.875	4
108	10420	3"	---	2	9	7.875	2.93 - 3.45	1.031	4
109	10430	3-1/2"	---	1	9	9.40	3.28 - 3.95	1.031	4
110	10440	4"	---	1	10	10.20	3.68 - 4.43	1.031	4