


Straight Blade Devices

30 Ampere, 125/250 Volts, 3Ø 250 and 3ØY 120/208 Volts AC

3 Pole, 4 Wire Grounding and 4 Pole, 4 Wire Non-Grounding

Single Receptacles and Plugs



HBL9430A

**30A, 125/250V
3 Pole, 4 Wire Grounding
Receptacles and Plugs**

IP20
SUITABILITY



**30A 125/250V
NEMA 14-30R
2(2) HP**



**30A 125/250V
NEMA 14-30P
2(2) HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	HBL9430A
Plug, nylon.	.625"-1.310" (15.9-33.3)	- HBL9431C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	- HBL9432C



HBL9431C

**30A, 3Ø 250V AC
3 Pole, 4 Wire Grounding
Receptacles and Plugs**

IP20
SUITABILITY




**30A 3Ø 250V AC
NEMA 15-30R
3 HP**



**30A 3Ø 250V AC
NEMA 15-30P
3 HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	HBL8430A
Plug, nylon.	.625"-1.310" (15.9-33.3)	- HBL8431C
Plug, nylon, angle, 4-position	.625"-1.310" (15.9-33.3)	- HBL8432C



HBL9432C

**30A, 3ØY 120/208V AC
4 Pole, 4 Wire Non-Grounding
Receptacles and Plugs**



IP20
SUITABILITY




**30A 3ØY
120/208V AC
NEMA 18-30R
UL Listed
3 HP**




**30A 3ØY
120/208V AC
NEMA 18-30P
UL Listed
3 HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	HBL8330A
Plug, nylon.	.625"-1.310" (15.9-33.3)	- HBL8331C

*Note: RTP is an abbreviation for reinforced thermoplastic polyester.
See page A-49 for accessories.*



HBL8330A



HBL8331C