


OCTRON T8 U-Shaped with 6" leg spacing (1" diameter)



OCTRON T8 U-shaped with 1-5/8" leg spacing (1" diameter)

CURVALUME® FLUORESCENT LAMPS
OCTRON® CURVALUME® U-SHAPED Lamps – 1 5/8" Leg Spacing

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Life @ 3hrs/ start IS	Life @ 12hrs/ start IS	Life @ 3hrs/ start PRS	Life @ 12hrs/ start PRS	CCT (K)	CRI	Approx Lumens Initial (Mean) @25°C/77°F	Notes
31	T8	22.5	22.6	Med Bipin	21877	FB031/830	15	15000	24000	20000	28000	3000	82	2725 (2560)	☼* / 3, 12,13,17,19,20
					21878	FB031/835	15	15000	24000	20000	28000	3500	82	2725 (2560)	☼* / 3, 12,13,17,19,20
					21879	FB031/841	15	15000	24000	20000	28000	4100	82	2725 (2560)	☼* / 3, 12,13,17,19,20
					21819	FB031/750	15	15000	24000	20000	28000	5000	75	2600 (2340)	☼* / 3, 12,13,17,19,20
16	T8	10.5	10.6	Med Bipin	21834	FB016/830	15	15000	24000	20000	28000	3000	82	1125 (1060)	☼ / 3,12, 13,17,19,20
					21835	FB016/835	15	15000	24000	20000	28000	3500	82	1125 (1060)	☼ / 3,12, 13,17,19,20
16	T8	10.5	10.6	Med Bipin	21836	FB016/841	15	15000	24000	20000	28000	4100	82	1125 (1060)	☼ / 3,12, 13,17,19,20
24	T8	16.5	16.6	Med Bipin	21874	FB024/830	15	15000	24000	20000	28000	3000	82	1925 (1810)	☼ / 3,12, 13,17,19,20
					21875	FB024/835	15	15000	24000	20000	28000	3500	82	1925 (1810)	☼ / 3,12, 13,17,19,20
					21876	FB024/841	15	15000	24000	20000	28000	4100	82	1925 (1810)	☼ / 3,12, 13,17,19,20

OCTRON® 800 XP® SUPERSAVER® CURVALUME® U-SHAPED ECOLOGIC® Lamps – 6" Leg Spacing

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Life @ 3hrs/ start IS	Life @ 12hrs/ start IS	Life @ 3hrs/ start PRS	Life @ 12hrs/ start PRS	CCT (K)	CRI	Approx Lumens Initial (Mean) @25°C/77°F	Notes
30	T8	22.5	22.6	Med Bipin	22170	FB030/830/XP/6/SS/ECO	16	18000	26000	24000	30000	3000	85	2800 (2630)	☼* / 3,12, 13,17,19,20,27
					22171	FB030/835/XP/6/SS/ECO	16	18000	26000	24000	30000	3500	85	2800 (2630)	☼* / 3,12, 13,17,19,20,27
					22172	FB030/841/XP/6/SS/ECO	16	18000	26000	24000	30000	4100	85	2800 (2630)	☼* / 3,12, 13,17,19,20,27
28	T8	22.5	22.6	Med Bipin	22303	FB028/830/XP/6/SS/ECO	16	18000	26000	24000	30000	3000	85	2590 (2435)	☼* / 3, 12,13,17,19,20,27
					22304	FB028/835/XP/6/SS/ECO	16	18000	26000	24000	30000	3500	85	2590 (2435)	☼* / 3, 12,13,17,19,20,27
					22305	FB028/841/XP/6/SS/ECO	16	18000	26000	24000	30000	4100	85	2590 (2435)	☼* / 3, 12,13,17,19,20,27

*means this bulb meets Federal minimum efficiency standards