



# Bolts

## MACHINE BOLTS, SQUARE HEAD (continued) CABLE A SUSPENSION BOLTS



**5/8" Bolt Head Size**



**3/4" Bolt Head Size**



### 5/8" Thread Diameter (5/8-11 UNC)

Catalog Number	Dimensions Inches		Approx Ship Wt lb Each	Cable A Suspension Bolt Catalog Number
	Length	Minimum Thread Length		
8802	2	1½	0.36	
880212	2½	1½	0.39	
PS8803	3	1½	0.48	
8804	4	3	0.57	
8805	5	3	0.60	
8806 <sup>(1) (2)</sup>	6	3	0.69	
8807 <sup>(1) (2)</sup>	7	3	0.75	
8808 <sup>(1) (2)</sup>	8	4	0.78	400013645
8809 <sup>(1)</sup>	9	4	0.88	
8810 <sup>(1) (2)</sup>	10	4	0.93	400013702
8812 <sup>(1) (2)</sup>	12	6	1.08	400013702
8814 <sup>(1) (2)</sup>	14	6	1.23	400013678
8816 <sup>(1) (2)</sup>	16	6	1.40	400013686
8818 <sup>(1) (2)</sup>	18	6	1.54	400013694
8820 <sup>(1)</sup>	20	6	1.71	400013702
8822 <sup>(1)</sup>	22	6	1.76	400013710
8824 <sup>(1)</sup>	24	6	1.96	400314274
8826	26	6	2.15	
8828	28	6	2.31	
8830	30	6	2.52	

### 3/4-Inch Thread Diameter (3/4-9 UNC)

Catalog Number	Dimensions Inches		Approx Ship Wt lb Each	Cable A Suspension Bolt Catalog Number
	Length	Minimum Thread Length		
PS8902	2	1¾	0.65	
PS8903	3	1¾	0.75	
PS8906	6	3	1.09	
PS8907	7	3	1.18	
8908 <sup>(1) (2)</sup>	8	4	1.26	
8910 <sup>(1) (2)</sup>	10	4	1.54	400013728
8912 <sup>(1) (2)</sup>	12	6	1.62	400013736
8914 <sup>(1) (2)</sup>	14	6	1.88	400013744
8916 <sup>(1) (2)</sup>	16	6	2.25	400013751
8918 <sup>(1) (2)</sup>	18	6	2.32	400013769
8920 <sup>(1)</sup>	20	6	2.52	
8922 <sup>(1)</sup>	22	6	2.68	400013022
8924 <sup>(1)</sup>	24	6	3.04	400013024
8926 <sup>(1)</sup>	26	6	3.08	
8928	28	6	3.23	
8930	30	8	3.46	
8932	32	8	3.69	

NOTE: 18,350 lb rated tensile strength.  
NOTE: Cable A Suspension Bolts include 2 square nuts  
(1) RUS listed, c - machine bolt.  
(2) ANSI standard, C-135.1.

NOTE: 12,400 lb rated tensile strength.  
NOTE: Cable A Suspension Bolts include 2 square nuts  
(1) RUS listed, c - machine bolt.  
(2) ANSI standard, C-135.1.