

Rigid/Intermediate Grade Conduit Fittings

Conduit Couplings



THREE PIECE CONDUIT COUPLINGS - MALLEABLE IRON

Applications:

- Used to join two lengths of threaded conduit. Couples conduit when conduit cannot be turned.

Standard Materials:

- Heavy duty casting

Standard Finishes:

- Zinc Plated


Options:

Mechanically galvanized

Suffix
HDG

Malleable Iron (Concrete Tight)

UL File No. E-19189



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
190M	1/2"	25	23
191	3/4"	25	35
192	1"	10	60
193	1 1/4"	5	91
194	1 1/2"	5	167
195	2"	5	215
196	2 1/2"	2	430
197	3"	1	463
198	3 1/2"	1	655
199	4"	1	800
188†	5"	1	1200
189†	6"	1	2100

†Not UL Listed

RIGID CONDUIT COUPLINGS - STEEL

Applications:

- Used to join two lengths of threaded rigid or IMC conduit. They can be used in both indoor and outdoor applications

Standard Materials:

- Galvanized steel

Galvanized steel



Cat. #	Size	Unit Qty.	Wt. Lbs. Per 100
RC50	1/2"	10	12
RC75	3/4"	10	18
RC100	1"	10	29
RC125	1 1/4"	5	38
RC150	1 1/2"	5	52
RC200	2"	5	69
RC250	2 1/2"	2	181
RC300	3"	1	220
RC350	3 1/2"	1	377
RC400	4"	1	298
RC500	5"	1	477
RC600	6"	1	684

CP