



BURNDY Catalog Number	AMS500
UPC Number	781810241059
Description	500-3/0 DUAL RATED SPLIC
Status	Active

Web Use  
BURNDY Product Line

Dimensional	
Width (in)	1.25
Length (in)	4.78
Hex Size	3/8
H1	1.38
General	
Number of Screws	4
Product Description	Aluminum Mechanical Splice, 500 kcmil-3/0 AWG, 13/16" Screw Dia, 4 Screws, 3/8" Hex Size, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	3/0 AWG-500 kcmil
Copper Solid Size (Range)	3/0 AWG-4/0 AWG
Copper Stranded (Range)	3/0 AWG-500 kcmil
Physical	
Installation Torque	375
Type of Plating	Tin
Connector Type	Splice, Reducer
Plated (Yes or No)	Y
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA  
47, industrial Park Drive  
Manchester NH03109

BURNDY Technical Servcies  
47, industrial Park Drive  
Manchester NH03109

Hours: 8.00 AM - 5.00 PM  
Monday - Friday  
Phone: 000-346-4175