
## Thomas@Betts





TB38-4X-G

**UPC Number:** 70450802598

Status: Active

**Description:** 


Features

Format-PDF

1 in. Dark Gray PVC Coated Type TB Form 8 UL-4X Gray Iron Conduit Body and Cover.

|     | _ | _  |       | _  | _ |    |
|-----|---|----|-------|----|---|----|
| ‡ L | 7 |    |       | 7) |   | ΙŢ |
| ĭL  | _ | 1  |       | 1  |   | Ιĭ |
|     |   | 7. | - F - | =  |   |    |
|     |   | 1  | – Ā - |    |   |    |

|             | UL Listed Type 4X and NEMA 4X rating for excellent protection in wash down areas, as well as harsh outdoor environments exposed to moisture, rain, ice or snow.         |
|-------------|---|
|             | Double coated superior corrosion protection, bodies and covers coated inside and out with .002 in. blue urethane, then exterior coated with a minimum of .040 in. PVC.  |
|             | PVC coated cast iron conduit body comes with mat-<br>ed cast iron cover, injection molded with an inte-<br>gral O-ring seal and stainless steel encapsulated<br>screws. |
| Application |   |



| Application                                     |   |
|---|---|
|   | Antonio del contesta formana di catalogia la l'ancida della d |
|   | Act as pull outlets for conductors being installed            |
|   | Provide openings for making splices and taps in               |
|   | conductors  |
|   | Connect conduit sections                                      |
|   | Provide taps for branch conduit runs                          |
|   | Make 90° bends in conduit runs                                |
|   | Provide for access to conductors for maintenance              |
|   | and future system changes                                     |
| General   |   |
| Custom_Finish                                   | f8tb1   |
| Trade Size (inches)                             | 1   |
| Material  | Gray Iron   |
| Finish  | PVC Coated  |
| Color   | Dark Gray   |
| Conduit Body Shape                              | ТВ  |
| Dimension Information                           |   |
| Dimension A (inches)                            | 7 5/16  |
| Dimension B (inches)                            | 3 1/4   |
| Dimension C (inches)                            | 1 3/4   |
| Dimension D (inches)                            | 1 3/8   |
| Dimension E (inches)                            | 4 9/16  |
| Technical Information                           |   |
| Chemical Resistance Chart                       | Available on Website  |
| Specifications                                  |   |
|   |   |
| Ocal Specification Guide-1995 Master            | Available on Website  |
| Format-PDF                                      |   |
| Ocal Specification Guide-1995 Master Format-DOC | Available on Website  |
| Ocal Specification Guide-2004 Master            | Available on Website  |

Available on Website



Ocal Specification Guide-2004 Master Format-DOC

| Packaging                              |                      |
|--|----------------------|
| Package in Units                       | 10                   |
| T&B Sold in UOM                        | Each                 |
| T&B Weight Per UOM                     | 3.85 lbs. Each       |
| Application Support                    |                      |
| Ocal Specifications                    | Available on Website |
| Recommended Installation Procedures    | Available on Website |
| Product Overview-Conduit Outlet Bodies | Available on Website |
| NEMA Standards-RN 1                    | Available on Website |
| NEC 310-16 - Conductors for General    | Available on Website |
| Wiring                                 |                      |
| NEC Table 8                            | Available on Website |
| Notes                                  |                      |

Dimensional values are of uncoated conduit bodies.

## Certifications





File Nbr: E 2969

## For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com