



GE
Lighting

38957 - Remote 4ft LED Plastic Tubes

LED15T8/4/835

- ☞ Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall.
- ☞ Each LED tube is operated by a GE Lighttech™ driver.
- ☞ 66% longer life than LFL (50,000 vs. 30,000 hours)
- ☞ Instant on light
- ☞ NSF Rated for food application (shatter resistant)
- ☞ Easy disposal, non-hazardous waste
- ☞ UL Listed
- ☞ DLC Listed

Product Photo



GENERAL CHARACTERISTICS

| | |
|--------------------------------|------------------|
| Dimmable | Yes |
| Product Technology | LED |
| Rated Life (Hours) | 50000 h |
| Dimmable / Non-Dimmable | Yes |
| LED Tube Type | Plastic |
| Environmental Rating | LED_Tube_Plastic |
| 10 Digit U | 4316838957 |
| Lamp Count | 1 |
| Life in Years | 45.7 yr |
| Requested Structure | Sleeve |
| Estimated Energy Cost per Year | 1.57 |
| Bulb Shape | T8 |

PHOTOMETRIC CHARACTERISTICS

| | |
|------------------------|---------|
| Rated Beam Spread | 13 W |
| Initial Lumens-nominal | 1750 lm |
| Color Temperature | 3500 K |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 38957 |
| Description | LED15T8/4/835 |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | 10 |
| Ean UPC | 043168389570 |
| Standard Package GTIN | 10043168389577 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 10 |
| Sales Unit | Case |
| UCC | 043168389570 |
| Alternative Unit Of Measure | EACH |
| Standard Package Quantity | 10 |
| Ean UPC | 043168389570 |
| Standard Package GTIN | 00043168389570 |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 10 |
| Sales Unit | Each |
| UCC | 043168389570 |

DIMENSIONS

| | |
|-----------------------------|---------|
| Bulb Max Overall Length-MOL | 48.0 in |
|-----------------------------|---------|

ELECTRICAL CHARACTERISTICS

| | |
|-------------------------|-------|
| Drive Current | 45.7 |
| Energy Efficiency Class | yr |
| Voltage <Nom> | 120 V |
| Rated power (Watts) | 13 W |

CAUTIONS & WARNINGS

Caution

Risk of Electric Shock

Suitable for damp locations

Not intended for use with emergency exit fixtures or emergency exit lights