



PULSE-GROUND FAULT LOCATOR

PULSE-GROUND FAULT LOCATOR

Cat No: PE2003

UPC No: 783310086666

### Description

---

- Identifies the exact location of even the smallest breaks in insulation by "pulsing" a high-voltage signal that radiates into the earth at the location of the faults. With the A-frame mounted receiver, a visual analog meter points the way to the source of the voltage
- Multiple faults on a single wire can be identified indicating the need to replace instead of repair
- Extra-long test leads feature heavy-duty alligator clips for use on multiple cable types
- Includes a rechargeable transmitter, receiver, A-frame, ground stake, 120V charger and a 12V DC (cigarette lighter) adapter
- Battery operated (one 12V and one 9V battery are included)
- Molded carrying case included

## Specifications

---

- Battery :
  - Transmitter: (1) 12 V Rechargeable Battery
  - Receiver: (1) 9 V Battery
- Battery Life :
  - Transmitter - 23 HR Per Charge
  - Receiver - 200 HR
- Construction :
  - Transmitter-Aluminum Housing In Polyethylene Case
  - Receiver-Powder Coated Aluminum
- Dimensions : 17.000 IN (421.000 MM) X 8.500 IN (215.000 MM) X 6.500 IN X(160.000 MM)  
Transmitter, 33.500 IN (840.000 MM) X 21.750 IN (550.000 MM) X 3.250 IN (8.000 MM) On A-  
Frame Receiver
- Model : PE2003
- Replacement Part :
  - 2000H Transmitter (IncludesCH1 And CH2)
  - 2000R Receiver
  - AF2 A-Frame
  - CH1 AC Charger
  - CH2 DC Charger
- Transmitter Power : 2400 VDC Peak
- Voltage Protection : 240 VAC/400 VDC
- Weight : 12.500 LB (5.700 KG)