

# SUFFIXES

## Quick Reference Table

Suffix	Description	Applicable Products	Special Instructions
-001	Reverse interior for PN, DSN24, DSN37 device only	PN, DSN24, DSN37	Add to inlet and receptacle part numbers
-026	Black device gasket	DS, DR, DSN	
-080	Junction box with angle	All	
-1	1" NPT thread size for conduit entry	DSN, DS, DR, DX, PN, DN, DB	Add to applicable accessories
-112	1 1/2" NPT thread size for conduit entry	DSN, DS, DR, DX, DN, DB	Add to applicable accessories
-12	1/2" NPT thread size for conduit entry	DS, DR, DX, DN, DB	Add to applicable accessories
-114	1 1/4" NPT thread size for conduit entry	DSN, DS, DR, DX, PN, DN, DXN, DB	Add to applicable accessories
-172	Two auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-173	Three auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-174	Four auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-175	Five auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-180	180° lid opening for flush mounted inlets	DS100, DS200, DR150, DR250	Add to receptacle part number
-185	High temp product	PN	Add to inlet or receptacle part number
-2	2" NPT thread size for conduit entry	DS, DR, DX, DN, DB	Add to applicable accessories
-200	Cable range for PF/PFQ Handle 2.000" - 2.125"	PF/PFQ	Add to handle part number
-20	2" NPT fitting size	PF/PFQ	Add to PF/PFQ junction box
-20P	Cable range .28" - .41"	DXN20, DXN30	Add to plug/connector part number
-212	2 1/2" NPT thread size for conduit entry	DS, DR, DN	
-225	Cable range for PF/PFQ Handle 2.125" - 2.375"	PF/PFQ	Add to handle part number
-237	Cable range for PF/PFQ Handle 2.25" - 2.375"	PF/PFQ	Add to handle part number
-25	2 1/2" NPT fitting size	PF/PFQ	Add to PF/PFQ junction box
-25P	Cable range .35" - .67"	DXN	Add to plug/connector part number
-250	Cable range for PF/PFQ Handle 2.375" - 2.25"	PF/PFQ	Add to handle part number
-262	Two auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-263	Three auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-264	Four auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet & receptacle part number
-270	Auxiliary switch for female devices	DS, DS, DR	Add to receptacle part number
-275	Cable range for PF/PFQ Handle 2.5" - 2.75"	PF/PFQ	Add to handle part number
-30	3" NPT fitting size	PF/PFQ	Add to PF/PFQ junction box
-300	Cable range for PF/PFQ Handle 2.75" - 3"	PF/PFQ	Add to handle part number
-30A	30A capacity for PN devices	PN	Add to inlet & receptacle part number
-312	Cable range for PF/PFQ Handle 3" - 3.125"	PF/PFQ	Add to handle part number
-32P	Cable range .43" - .83"	DXN	Add to plug/connector part number
-335	Cable range for PF/PFQ Handle 3.125" - 3.35"	PF/PFQ	Add to handle part number
-338	PRL release pawl	DSN,DS20,DS30,DS60,DS100C,DS100,DN	Add to inlet part number
-338-A188	PRL release pawl with straight insertion	DS200	Add to inlet part number
-34	3/4" NPT thread size for conduit entry	DSN, DS, DR, DX, PN, DN, DXN, DB	Add to applicable accessories
-348-A188	SRL release pawl w/straight insertion for receptacles	DS200	Add to receptacle part number
-352	Straight insertion	DSN,DS20,DS30,DS60,DS100C,DS100,DN	Add to inlet part number

Suffix	Description	Applicable Products	Special Instructions
-354	SRL release pawl w/straight insertion for receptacles	DSN,DS20,DS30,DS60,DS100C,DS100,DN	Add to receptacle part number
-35	3 1/2" NPT fitting size	PF/PFQ	Add to PF/PFQ junction box
-350	Cable range for PF/PFQ Handle 3.35" - 3.5"	PF/PFQ	Add to handle part number
-375	Mushroom Pawl	DSN, DS, DR	Add to receptacle part number
-375-843	Padlockable Mushroom Pawl	DSN, DS, DR, DN	Add to receptacle part number
-3NF	Non functioning contact to activate auxiliary switch	DSN, DS	Activates 2 Pole 4 Wire receptacle
-40	4 NPT fitting size	PF/PFQ	Add to PF/PFQ junction box
-40P	Cable range .75" - 1.10"	DXN	Add to plug/connector part number
-473	Finger drawplate on handle	DS	Add to handle part number
-48	Inlet or receptacle without cap	PF, DB	Add to inlet and receptacle part numbers
-4X	Type 4X watertightness	DS, DR	
-601	Special adapter plate for DSN1 angle on junction box	DSN20	
-824	Metal pawl for poly receptacles	DSN, DS, DR	
-824-300	Locking pawl	PN	Add to receptacle part number
-843	Padlock pawl	DSN, DS, DR	Add to receptacle part number
-845	Oversize padlock pawl	DS, DR	Add to receptacle part number
-924	Metal pawl for poly receptacles	DXN	Add to receptacle part number
-972	Two auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet and receptacle part numbers
-973	Three auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet and receptacle part numbers
-974	Four auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet and receptacle part numbers
-975	Five auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet and receptacle part numbers
-976	Six auxiliary pilot contacts	Select DSN, DS, DR models	Add to inlet and receptacle part numbers
-A06	Allows up to 4/0 AWG wiring capacity	DS200, DR250	Add to inlet and receptacle part numbers
-A155	Inlet without the standard lockout hole	DSN, DS	Add to inlet part number
-A188	Straight insertion	DS200	Add to inlet and receptacle part numbers
-B	Bottom interior piece	All	
-CG	Cable guide for PRL or SRL release pawl for handle	DSN, DS, DN	Add to handle part number
-C-***	Suffixes for DS100C inlets & receptacles	DS	Included in inlet/receptacle part number
-E323	Allows up to 2/0 AWG wiring capacity	DS100, DR150	
-HP	High pressure water protection	DN	Add to inlet and receptacle part numbers
-K**	Voltage being used when notching position is not standard	All	Add to inlet and receptacle part numbers
-LC	Less cover	DSN, DS	Add to receptacle part number
-MTR	Phase Rotation Meter	DSN, DS, DR, DB	Add to plug
-NC	Normally closed lid	DSN, DS, DR, DN	Add to receptacle part number
-NNF	Non functioning neutral - activates 3 Pole 4 Wire receptacle	DSN, DS, DR	Add to inlet part number
-NP	No paint on accessories	All accessories	
-R	Normally closed lid	DXN	Add to receptacle part number
-SS	Stainless Steel	PN7, PN12, DS	
-T	Top Interior piece	All	