


T12 Medium Bipin (1-1/2" diameter)



U-Shaped T12 (1-1/2" diameter)

## T12 RAPID START LAMPS

### 3-Foot SUPERSAVER® Rapid Start Lamps

| Nominal Wattage | Bulb | Nominal Length (in) | MOL (in) | Base      | Product Number | Ordering Abbreviation                              | Pkg Qty | Average Rated Life   |       | CCT (K) | CRI | Approx Lumens Initial (Mean) 25°C/77°F | Notes             |
|-----------------|------|---------------------|----------|-----------|----------------|--|---------|----------------------|-------|---------|-----|--|-------------------|
|                 |      |                     |          |           |                |  |         | Hours per start 3hrs | 12hrs |         |     |  |                   |
| 25              | T12  | 36                  | 35.78    | Med Bipin | 23473          | F25T12/WW/RS/SS<br><i>formerly F30T12/WW/RS/SS</i> | 30      | 18000                | 28800 | 3000    | 52  | 1975 (1680)                            | /3,7,<br>12,13,17 |
|                 |      |                     |          |           | 23472          | F25T12/CW/RS/SS<br><i>formerly F30T12/CW/RS/SS</i> |         |                      |       |         |     |  |                   |

### 3-Foot Standard Rapid Start Lamps

| Nominal Wattage | Bulb | Nominal Length (in) | MOL (in) | Base      | Product Number | Ordering Abbreviation | Pkg Qty | Average Rated Life |  | CCT (K) | CRI | Approx Lumens Initial (Mean) 25°C/77°F | Notes           |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |
|-----------------|------|---------------------|----------|-----------|----------------|-----------------------|---------|--------------------|--|---------|-----|--|-----------------|----|-------|------|----|-------------|-----------------|----|-------|------|----|-------------|-----------------|----|-------|------|----|-------------|-----------------|----|-------|------|----|-------------|-----------------|
|                 |      |                     |          |           |                |                       |         | 3 Hours per start  |  |         |     |  |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |
| 30              | T12  | 36                  | 35.78    | Med Bipin | 23482          | F30T12/WW/RS          | 30      | 18000              |  | 3000    | 52  | 2275 (1935)                            | /3,<br>12,13,17 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |
|                 |      |                     |          |           | 23474          | F30T12/D830/RS        |         |                    |  |         |     |  |                 | 30 | 18000 | 3000 | 80 | 2290 (2060) | /3,<br>12,13,17 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |
|                 |      |                     |          |           | 23484          | F30T12/D35/RS         |         |                    |  |         |     |  |                 |    |       |      |    |             |                 | 30 | 18000 | 3500 | 70 | 2250 (1980) | /3,<br>12,13,17 |    |       |      |    |             |                 |    |       |      |    |             |                 |
|                 |      |                     |          |           | 23139          | F30T12/D835/RS        |         |                    |  |         |     |  |                 |    |       |      |    |             |                 |    |       |      |    |             |                 | 30 | 18000 | 3500 | 80 | 2290 (2060) | /3,<br>12,13,17 |    |       |      |    |             |                 |
|                 |      |                     |          |           | 23476          | F30T12/CW/RS          |         |                    |  |         |     |  |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 | 30 | 18000 | 4200 | 60 | 2200 (1870) | /3,<br>12,13,17 |
|                 |      |                     |          |           | 23478          | F30T12/D/RS           |         |                    |  |         |     |  |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |    |       |      |    |             |                 |

### CURVALUME® SUPERSAVER® Rapid Start ECOLOGIC® Lamps – U-Shaped, 6" Leg Spacing

| Nominal Wattage | Bulb | Nominal Length (in) | MOL (in) | Base      | Product Number | Ordering Abbreviation                                | Pkg Qty | Average Rated Life |  | CCT (K) | CRI | Approx Lumens Initial (Mean) 25°C/77°F | Notes                  |    |       |      |    |             |                        |
|-----------------|------|---------------------|----------|-----------|----------------|--|---------|--------------------|--|---------|-----|--|------------------------|----|-------|------|----|-------------|------------------------|
|                 |      |                     |          |           |                |  |         | 3 Hours per start  |  |         |     |  |                        |    |       |      |    |             |                        |
| 34              | T12  | 23                  | 22.60    | Med Bipin | 24052          | FB34/WW/6/SS/ECO<br><i>formerly FB40/WW/6/SS/ECO</i> | 12      | 18000              |  | 3000    | 52  | 2650 (2280)                            | * /3,<br>8,12,13,17,36 |    |       |      |    |             |                        |
|                 |      |                     |          |           | 24065          | FB34/D35/6/SS<br><i>formerly FB40/D35/SS</i>         |         |                    |  |         |     |  |                        | 12 | 18000 | 3500 | 70 | 2730 (2460) | * /3,<br>8,12,13,17,36 |
|                 |      |                     |          |           | 24054          | FB34/CW/6/SS/ECO<br><i>formerly FB40/CW/6/SS/ECO</i> |         |                    |  |         |     |  |                        |    |       |      |    |             |                        |

### CURVALUME® Standard Rapid Start Lamps – U-Shaped, 6" Leg Spacing

| Nominal Wattage | Bulb | Nominal Length (in) | MOL (in) | Base      | Product Number | Ordering Abbreviation | Pkg Qty | Average Rated Life |  | CCT (K) | CRI | Approx Lumens Initial (Mean) 25°C/77°F | Notes                |    |       |      |    |             |                      |    |       |      |    |             |                      |
|-----------------|------|---------------------|----------|-----------|----------------|-----------------------|---------|--------------------|--|---------|-----|--|----------------------|----|-------|------|----|-------------|----------------------|----|-------|------|----|-------------|----------------------|
|                 |      |                     |          |           |                |                       |         | 3 Hours per start  |  |         |     |  |                      |    |       |      |    |             |                      |    |       |      |    |             |                      |
| 40              | T12  | 23                  | 22.60    | Med Bipin | 24080          | FB40/D30/6            | 12      | 18000              |  | 3000    | 70  | 3050 (2745)                            | * /3,<br>12,13,17,36 |    |       |      |    |             |                      |    |       |      |    |             |                      |
|                 |      |                     |          |           | 24017          | FB40/D830/6           |         |                    |  |         |     |  |                      | 12 | 18000 | 3000 | 80 | 3200 (2880) | * /3,<br>12,13,17,36 |    |       |      |    |             |                      |
|                 |      |                     |          |           | 24081          | FB40/D35/6            |         |                    |  |         |     |  |                      |    |       |      |    |             |                      | 12 | 18000 | 3500 | 70 | 3050 (2745) | * /3,<br>12,13,17,36 |
|                 |      |                     |          |           | 24082          | FB40/D41/6            |         |                    |  |         |     |  |                      |    |       |      |    |             |                      |    |       |      |    |             |                      |

\*means this bulb meets Federal minimum efficiency standards

For the current listing of available products and more complete product information, please visit us at [www.sylvania.com](http://www.sylvania.com). Specifications subject to change without notice.