



1492-H...

1492-WFB4...

Dimensions are not intended to be used for manufacturing purposes.  
Note: Height dimension is measured from top of rail to top of terminal block.



**Specifications**

Single-circuit fusible terminal block with or without fuse indication.

Single-circuit fuse block with or without fuse indication.

| Certifications                   |  | CSA                          | IEC             |  | CSA         | IEC        |
|----------------------------------|-----------------------------------------------------------------------------------|------------------------------|-----------------|-------------------------------------------------------------------------------------|-------------|------------|
|                                  | H6/WFB4                                                                           | 300V AC/DC                   | 500V AC/DC      | 300V AC/DC                                                                          |             | 500V AC/DC |
| Voltage Rating                   | H5/WFB424                                                                         | 10...57V AC/DC               |                 | 10...57V AC/DC                                                                      |             |            |
|                                  | H4/WFB4250                                                                        | 100...300V AC                |                 | 85...264V AC                                                                        |             |            |
| Maximum Current                  |                                                                                   | 15 A                         |                 | 15 A                                                                                | 15 A *      |            |
| Wire Range (Rated Cross Section) |                                                                                   | #30...12 AWG                 | 0.5...<br>4 mm² | #30...12 AWG                                                                        | 0.5...4 mm² |            |
| Wire Strip Length                |                                                                                   | 0.38 in. (9.7 mm)            |                 | 0.31 in. (8 mm)                                                                     |             |            |
| Recommended Tightening Torque    |                                                                                   | 7.1 lb•in (0.8 N•m)          |                 | 2.65...5.3 lb•in (0.3...0.6 N•m)                                                    |             |            |
| Density                          |                                                                                   | 33 pcs/ft (109pcs /m)        |                 | 38 pcs/ft (125 pcs/m)                                                               |             |            |
| Housing Temperature Range        |                                                                                   | -40...+195 °F (-40...+90 °C) |                 | -40...+195 °F (-40...+90 °C)                                                        |             |            |
| Indicator Type                   |                                                                                   |                              |                 |                                                                                     |             |            |
| H6/WFB4                          |                                                                                   | Non-Indicating               |                 | Non-Indicating                                                                      |             |            |
| H5/WFB424                        |                                                                                   | Red LED                      |                 | Red LED                                                                             |             |            |
| H4/WFB4250                       |                                                                                   | Neon                         |                 | Neon                                                                                |             |            |
| Leakage Current                  |                                                                                   |                              |                 |                                                                                     |             |            |
| H6/WFB4                          |                                                                                   | —                            |                 | —                                                                                   |             |            |
| H5/WFB424                        |                                                                                   | 2 mA @ 24V                   |                 | 2 mA @ 24V                                                                          |             |            |
| H4/WFB4250                       |                                                                                   | 2 mA @ 300V                  |                 | 2 mA @ 300V                                                                         |             |            |
| Fuse Size (Not Supplied)         |                                                                                   | 1/4 x 1-1/4 in.              |                 | 5 x 20 mm                                                                           |             |            |
| Short-Circuit Current Rating     |                                                                                   | See page 12-42               |                 |                                                                                     |             |            |

| Terminal Blocks                      | Cat. No.              | Pkg Qty. | Cat. No.              | Pkg Qty. |
|--------------------------------------|-----------------------|----------|-----------------------|----------|
| Color: Black No-indication           | 1492-H6               | 25       | 1492-WFB4             | 50       |
| Black w/LED                          | 1492-H5               | 25       | 1492-WFB424           | 50       |
| Black w/Neon                         | 1492-H4               | 25       | 1492-WFB4250          | 50       |
| Accessories                          | Cat. No.              | Pkg Qty. | Cat. No.              | Pkg Qty. |
| Mounting Rails:                      |                       |          |                       |          |
| 1 m Symmetrical DIN (Steel)          | 199-DR1               | 10       | 199-DR1               | 10       |
| 1 m Symmetrical DIN (Aluminum)       | 1492-DR5              | 10       | 1492-DR5              | 10       |
| 1 m Hi-Rise Sym. DIN (Aluminum)      | 1492-DR6              | 2        | 1492-DR6              | 2        |
| 1 m Angled Hi-Rise Sym. DIN (Steel)  | 1492-DR7              | 2        | 1492-DR7              | 2        |
| 3 ft Scored A-B Rail                 | 1492-N1               | 20       | —                     | —        |
| 3 ft Rigid A-B Rail                  | 1492-N22              | 20       | —                     | —        |
| 3 ft High Rise A-B Rail              | 1492-N44              | 2        | —                     | —        |
| Standoff Brackets (Use Every 12 in.) | 1492-N25              | 2        | —                     | —        |
| End Barrier                          | 1492-N37              | 50       | Not Required          | —        |
| End Anchors and Retainers:           |                       |          |                       |          |
| Screwless End Retainer               | 1492-ERL35            | 20       | 1492-ERL35            | 20       |
| DIN Rail — Normal Duty               | 1492-EAJ35            | 100      | 1492-EAJ35            | 100      |
| DIN Rail — Heavy Duty                | 1492-EAHJ35           | 50       | 1492-EAHJ35           | 50       |
| A-B Rail — Heavy Duty                | 1492-N23              | 10       | —                     | —        |
| 10-Pole Side Jumper *                | 1492-N49              | 10       | 1492-SJFB8-10         | 10       |
| Side Jumper Insulating Sleeve        | 1492-SJS              | 10       | —                     | —        |
| Other Accessories:                   |                       |          |                       |          |
| Partition Plate                      | —                     | —        | 1492-PPSL3            | 50       |
| Marking Systems:                     |                       |          |                       |          |
| Snap-In Marker Card — For Base Block | —                     | 5        | 1492-MS8X12 (56/card) | 5        |
|                                      | —                     | 5        | 1492-MS8X9 (56/card)  | 5        |
| For Handle                           | 1492-MS8X12 (56/card) | 5        | 1492-MS8X9 (56/card)  | 5        |
|                                      | 1492-MS8X9 (56/card)  | 5        |                       |          |
| Adhesive Labels                      | 1492-ALHFB (50/sheet) | 1        | 1492-ALHFB (50/card)  | 1        |

\* IEC standards for 5 x 20 mm fuses do not include ratings above 6.3 A.

\* Cat. No. 1492-N49 is uninsulated. Cat. No. 1492-SJFB8-10 is insulated.