

ELECTRONIC FLUORESCENT BALLASTS

For 25W-36" T8 Lamps

HIGH POWER FACTOR SOUND RATED A



No. of Lamps	Input Volts	Lamp Starting Method	Ballast Family	Catalog Number	Input Power ANSI (Watts)	Ballast Factor	Max. THD %	Line Current (Amps)	Min. Starting Temp. (°F/°C)	Dim.	Wiring Dia.	
F25T8, FBO24T8 (25W - 36")												
1	120	IS	AmbiStar [‡]	REB-2P32-SC	26	1.00	150	0.39	0/-18	B	*64	
	120-277	IS	Centium	ICN-132-MC	23	0.88	15	0.19-0.09	0/-18	A2	63	
				ICN-1P32-N	26	0.91	10	0.22-0.10		N	*64	
				ICN-2P32-N	29	1.06	15	0.24-0.11				
			Optanium	IOP-1P32-LW-N	21	0.78	10	0.17-0.08	-20/-29	N	63	
				IOPA-1P32-LW -N								
				IOP-1P32-N	23	0.88	10	0.20-0.09		N		
				IOPA-1P32-N						B		
				IOP-1P32-HL-SC	30	1.22	10	0.26-0.11		N		
				IOPA-1P32-HL-N								
				IOP-2P32-LW-N	24	0.90	10	0.20-0.09		N	*64	
				IOPA-2P32-LW-N								
				IOP-2P32-N	28	1.05	10	0.23-0.10				
				IOPA-2P32-N								
				IOP-2P32-HL-N	35	1.40	20	0.29-0.13				
				IOPA-2P32HL-N								
		PS	IOP-1PSP32-LW-N	20	0.74	10	0.16-0.07	0/-18	N	20		
			IOP-1PSP32-N	22	0.92	10	0.19-0.08			77		
			IOP-2PSP32-LW-N	21	0.77	10	0.17-0.08					
			IOP-2PSP32-N	25	0.97	10	0.21-0.10					
			IOP-2PSP32-HL-N	35	1.35	10	0.29-0.13					
	347	IS	Optanium	GOPA-1P32-LW-SC	20	0.80	10	0.07	-20/-29	B	63	
				GOPA-1P32-SC	22	0.91		0.07			*64	
				GOPA-2P32-LW-SC	24	0.88		0.08				
				GOPA-2P32-SC	27	1.05		0.08				
				GOP-2PSP32-LW-SC	26	0.77		0.08				
				GOP-2PSP32-SC	26	1.05		0.08				0/-18
	PS	HOP-2PSP32-HL-L		35	1.30	0.11-0.09		L				

[‡] The above AmbiStar ballasts are normal power factor and labeled 'For Residential Use Only'

Refer to page 3-38 and 3-39 for dimensions

Refer to page 3-40 and 3-41 for wiring diagrams

Refer to pages 9-23 to 9-27 for lead lengths and shipping data