



2217-20

2217-20NST  
(/Products/Instruments/Digital-Multimeters/2217-20NST)

## True RMS Multimeter

★★★★★ 4.5 (2) Write a review

The Milwaukee True RMS Multimeter is a heavy duty meter for professional residential, commercial and industrial applications. The perfect tool for professional electricians, the 2217-20 offers functionality users expect with features that make doing the job easier. The 2217-20 True RMS Multimeter features a large white on black display for clearer readings, a slide rail system to add proprietary accessories and rugged over-molding for increased durability and grip. The meter is rated to CATIII 600V and meets UL safety specifications required by electrical users. This meter is covered by Milwaukee's 5-Year Warranty.

Close

### INCLUDES:

- (1) True RMS Multimeter (2217-20) (/Products/Instruments/Digital-Multimeters/2217-20)
- (1) Electrical Test Lead Set
- (1) Dual Banana Thermocouple
- (2) AA Batteries

Read More

Where To Buy

### KEY FEATURES

Wide Voltage range to 600 volts AC/DC

### SPECIFICATIONS

Auto range to millivolts and milliamp ranges

### REVIEWS

True RMS for accurate measurement in all applications

Lo-Z measurement to eliminate ghost voltage

Frequency measurements from 10Hz to 50kHz

Contact temperature measurement from -40 to 752°F

Current Measurement to 10 amps AC/DC

High Contrast, White on Black Display with Backlight for easy reading

Rugged over-molding increases durability and user grip

↓ [Download Owner's Manual \(https://documents.milwaukeetool.com/58-14-2219d6.pdf\)](https://documents.milwaukeetool.com/58-14-2219d6.pdf)

↓ [Download Service Parts List \(/support/manuals-and-downloads?search=2217-20\)](/support/manuals-and-downloads?search=2217-20)

## PRODUCT SPECIFICATIONS

Display Type	White on Black LCD
Switch Type	Dial
Tool Warranty	5 Years
Battery Type	Alkaline (AA)
TRMS	Yes
Current AC DC	10.00A
Voltage AC DC	600V
Frequency	10 Hz - 50.00 kHz
Resistance	40MΩ
Continuity	Audible
Capacitance	1,000μF
Contact Temperature	-40° F to 752° F (-40° C to 400° C)
Safety Category Rating	CAT III 600V
Lo Z	Yes
Backlight	Yes
HOLD MIN MAX	Yes
Bargraph	Yes
Rugged Overmolding	Yes

---

Accessory Attachment	Magnetic Meter Holder
Calibration Needed	Yes - Recommend calibration service once every year
Length	6-1/2"

---