

Liquidtight Cord Grips

PG Hubs - 6/6 Nylon

Features


- PG threads
- Liquidtight at up to 70 P.S.I. water pressure
- Acme threads on body prevent skipping and speed installation
- Multiple sizes for cable diameters
- Suitable for NEMA type 6 enclosures
- IP68 Rating

Application

- Indoor or outdoor use
- Prevents cable pullout and controls arc of bend

Standard Material

- 6/6 nylon



Catalog Number	UPC	Size	Cable Diameter		Suggested Clearance Hole Diameter (inches)	Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.					A	B
LTF7	30230	PG7	.114	.25	.492	100	1000	1	1.17	.59
LTF9	30240	PG9	.181	.312	.599	25	100	2	1.30	.75
LTF11	30250	PG11	.23	.395	.733	25	100	3	1.46	.86
LTF13	30260	PG13	.17	.45	.804	25	100	3	1.41	.95
LTF16	30270	PG16	.23	.53	.886	---	50	4	1.66	1.05
LTF21	30280	PG21	.45	.705	1.12	10	100	6	1.87	1.30
LTF29	30290	PG29	.59	.99	1.47	10	100	6	2.23	1.66