



Twist-Lock® Devices
15 Ampere, 125 Volts
 2 Pole, 2 Wire, Non-Grounding
**Insulgrip® Plugs, Flanged Inlets,
 Connector Bodies and Receptacles**

IP20
 SUITABILITY



Plugs

Description	Cord Dia.	Catalog Number
Black and white nylon, polarized. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7545C

Accessories on page B-49.




HBL7545C

Flanged Inlets

Description	Catalog Number
Nylon casing, polarized, backwired, Multiple drive screws.	HBL7524C

Accessories on page B-48.




HBL7524C

Connector Bodies

Description	Cord Dia.	Catalog Number
Black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7506C

Accessories on page B-49.




HBL7506C

Receptacles

Description	Catalog Number
Duplex, flush, black phenolic.	HBL7540
Single, flush, black phenolic.	HBL7535
Single, panel mount, 1 1/4" (49.2) centers, black phenolic.	HBL7498

Accessories on pages B-48 and B-49.




HBL7540

Flanged Receptacles


Description	Catalog Number
Insulgrip nylon casing, backwired. Multiple drive screws.	HBL7526C
Metal flange, stainless steel casing, black phenolic, exposed terminals.	HBL7526

Accessories on pages B-48 and B-49.


Note: Only receptacles and plugs are HP rated.
 HP ratings are AC only.



HBL7526C



HBL7498



HBL7535

