

90° Connectors



Zinc Die Cast

Catalog Number	Size K.O.	Flex Size	Range		Ami. Unit	Amt. Std.	Weight Per C
			Min.	Max.			
801-DC2	1/2"	3/8"	.500"	.625"	25	250	11.8
804-DC2	1/2"	1/2"	.750"	.875"	25	100	15.3
806-DC2	3/4"	3/4"	.875"	1.000"	10	50	22.0
807-DC2	1"	1"	1.187"	1.312"	Bulk	25	36.0
808-DC2	1 1/4"	1 1/4"	1.500"	1.625"	Bulk	25	66.4
809-DC2	1 1/2"	1 1/2"	1.850"	1.950"	Bulk	5	136.0
810-DC2	2"	2"	2.350"	2.450"	Bulk	5	146.0

Zinc Die Cast with Insulated Throat

Catalog Number	Size K.O.	Flex Size	Range		Amt. Unit	Amt. Std.	Weight Per C
			Min.	Max.			
801-DCI2	1/2"	3/8"	.500"	.625"	25	250	11.7
804-DCI2	1/2"	1/2"	.750"	.875"	25	100	15.0
806-DCI2	3/4"	3/4"	.875"	1.000"	10	50	24.4
807-DCI2	1"	1"	1.187"	1.312"	Bulk	25	60.0
808-DCI2	1 1/4"	1 1/4"	1.500"	1.625"	Bulk	25	64.0
809-DCI2	1 1/2"	1 1/2"	1.850"	1.950"	Bulk	5	140.0
810-DCI2	2"	2"	2.350"	2.450"	Bulk	5	150.0



Highlighted catalog numbers are furnished with 2-way Phillips/Slotted Head screw.

Application

90° fitting with cover used for connecting flexible metal conduit to box or enclosure. 804- thru 808-DC2 & DCI2 also suitable for use with armored cable.

Material

Zinc die cast, optional insulated throat rated 105°C

Standard Finish

Ball burnished, mirror smooth

Dimensions

Refer to dimension section of catalog page 547

Certifications


® File No. E9391: 801-, 809-, 810- DC2 & DCI2

® File No. E20534: 804-, 806-, 807-, 808-DC2 & DCI2

<\$ File No. LR39354

Federal Spec. A-A-50552

90° Connectors



Zinc Die Cast

Catalog Number	Size K.O.	Flex Size	Metal Clad Cable Range		Amt. Unit	Amt. Std.	Weight Per C
			Min.	Max.			
801-DC2	1/2"	3/8"	.500"	.625"	25	250	11.8
804-DC2	1/2"	1/2"	.750"	.875"	25	100	15.3
806-DC2	3/4"	3/4"	.875"	1.000"	10	50	22.0
807-DC2	1"	1"	1.187"	1.312"	Bulk	25	36.0
808-DC2	1 1/4"	1 1/4"	1.500"	1.625"	Bulk	25	66.4

Zinc Die Cast with Insulated Throat

Catalog Number	Size K.O.	Flex Size	Metal Clad Cable Range		Amt. Unit	Amt. Std.	Weight Per C
			Min.	Max.			
801-DC12	1/2"	3/8"	.500"	.625"	25	250	11.7
804-DC12	1/2"	1/2"	.750"	.875"	25	100	15.0
806-DC12	3/4"	3/4"	.875"	1.000"	10	50	24.0
807-DC12	1"	1"	1.187"	1.312"	Bulk	25	60.0
808-DC12	1 1/4"	1 1/4"	1.500"	1.625"	Bulk	25	64.0



Highlighted catalog numbers are furnished with 2-way Phillips/Slotted Head screw.

90° Connector, Snap-In

Zinc Die Cast

Catalog Number	Size K.O.	Flex Size	Metal Clad Cable Range		Amt. Unit	Amt. Std.	Weight Per C
			Min.	Max.			
801-DCS	1/2"	3/8"	.500"	.625"	25	250	11.5

Zinc Die Cast with Insulated Throat

Catalog Number	Size K.O.	Flex Size	Metal Clad Cable Range		Amt. Unit	Amt. Std.	Weight Per C
			Min.	Max.			
801-DCSI	1/2"	3/8"	.500"	.625"	25	250	11.8

Available Spring 2000

Application

90° fitting with cover for connecting steel and aluminum interlocked armor or corrugated sheath metal clad cable to box or enclosure.

Material

Zinc die cast with optional insulated throat rated 105°C

Standard Finish

Ball burnished, mirror smooth

Dimensions

Refer to dimension section of catalog page 547

Certifications

© File No. E9391: 801-, 809-, 810- DC2 & DC12


® File No. E20534: 804-, **806-**, 807-, 808- DC2 & DC12



File No. LR39354

Federal Spec. A-A-50552

NEW



Application

90° fitting for connecting steel and aluminum interlocked or corrugated sheath metal clad cable to box or enclosure. Low profile, spring steel locking ring eliminates need for locknut, simply push into knockout.

Material

Zinc die cast with steel cover and locking ring. Optional insulated throat rated 105°C.

Standard Finish

Ball burnished, mirror smooth.

Certifications

© File No. E9391

(2) File No. LR39354

Federal Spec. A-A-50552