

FEATURES & BENEFITS – STANLEY® FATMAX® SCREWDRIVERS

- Ergonomically designed tri-lobular handle provides more torque than traditional-style screwdrivers for less effort.
- High strength polypropylene handle has textured rubber grip for comfort.
- Magnetic tips help secure grip on fasteners.
- Color-coded handles for easy tip identification.
- Chrome plated bars resist corrosion.
- Bars are fully ground and polished.
- Bars are made of alloy steel and heat treated for strength and durability.
- Shot blasted black oxide tips provide a more precise fit and a textured surface, which provides increased grip and less cam-out when in use.
- Tip identification symbol molded onto side of handle makes tip identification easy.



Phillips® is a registered trademark of Phillips Screw Co. Torx® is a registered trademark of Acument Intellectual Properties, LLC

11 PIECE STANLEY® FATMAX® SCREWDRIVER SET



Product #: 62-502

Contents	Description
62-552	⊖ 1/4 in Standard Slotted Tip (Stubby)
62-553	⊖ 1/4 x 4 in Standard Slotted Tip
62-555	⊖ 5/16 x 6 in Standard Slotted Tip
62-551	⊖ 1/8 x 3 in Cabinet Slotted Tip (Precision Pocket)
62-554	⊖ 3/16 x 3 in Cabinet Slotted Tip
62-556	⊕ #0 x 2-1/4 in Phillips® Tip
62-560	⊕ #2 Phillips® Tip (Stubby)
62-559	⊕ #1 x 3 in Phillips® Tip
62-561	⊕ #2 x 4 in Phillips® Tip
62-562	⊕ #3 x 6 in Phillips® Tip
65-033	⊕ ⊖ 2 Pt. Phillips® & 1/4 in Slotted Hybrid Offset



STANLEY® FATMAX® STANDARD SLOTTED TIP PRECISION POCKET SCREWDRIVERS



Product #	Tip Size	Blade Length	Blade Diameter	Overall Length
62-551	⊖ 1/8 in (3 mm)	3 in (76 mm)	1/8 in (3 mm)	6-1/2 in (165 mm)
62-556	⊕ #0	2-1/4 in (57 mm)	1/8 in (3 mm)	5-1/2 in (140 mm)

STANLEY® FATMAX® STUBBY SCREWDRIVERS



- Designed for close-quarter driving.



Product #	Tip Size	Blade Length	Blade Diameter	Overall Length
62-552	⊖ 1/4 in (6 mm)	1-3/4 in (44 mm)	1/8 in (3 mm)	4 in (102 mm)
62-560	⊕ #2	1-3/4 in (44 mm)	1/8 in (3 mm)	4 in (102 mm)

