


1492-FB Specifications

Product Type (n = number of poles)		M	CC	J30	J60
		1492-FBnM30 "B" 1492-FB1M30-D1 "B" 1492-FBnM30-L "B"	1492-FBnC30 "B" 1492-FB1C30-D1 "B" 1492-FBnC30-L "B"	1492-FBnJ30 "B" 1492-FBnJ30-L "B"	1492-FBnJ60 "B" 1492-FBnJ60-L "B"
For Fuse Type:		Midget 13/32" x 1-1/2" (10 x 38 mm)	Class CC	Class J	
Maximum voltage AC/DC		600V, 690V(IEC)	600V	600V	
Maximum current		30 A, 32 A (IEC)	30 A	30 A	60 A
Maximum current withstand (UL/CSA)		Fuse dependent 50 kA max UL	200 kA sym	200 kA sym	
Operating temperature range		-4...+130 °F, -20...+55 °C			
Conductor material		Copper, stranded			
Conductor strip length		0.43 in. (11 mm)		0.79 in. (20 mm)	
Conductor range	1 wire per terminal	#18...4 AWG (0.75...25 mm²)		#18...1 AWG (0.75...50 mm²)	#14...1 AWG (2.5...50 mm²)
	2 wires ★ per terminal	#18...8 AWG (0.75...10 mm²)		#18...6 AWG (0.75...16 mm²)	#14...6 AWG (2.5...16 mm²)
Terminal tightening torque		#18...8 AWG: 22 lb•in #6...4 AWG: 26 lb•in 0.75...25 mm²: 2.5 N•m		35 lb•in (4 N•m)	

★ Both wires must be same size

Approximate Dimensions

Note: Dimensions are shown in inches (mm). Dimensions are not intended for manufacturing purposes.



Dimension		For Midget Fuse	For Class CC Fuse	For Class J Fuse	
		30 A	30 A	30 A	60 A
Height		3.19 in. (81 mm)	3.19 in. (81 mm)	4.65 in. (118 mm)	4.65 in. (118 mm)
Depth		2.51 in. (64 mm)	2.51 in. (64 mm)	2.76 in. (70 mm)	3.23 in. (82 mm)
Width	1-Pole	0.71 in. (18 mm)	0.71 in. (18 mm)	1.41 in. (36 mm)	1.57 in. (40 mm)
	2-Pole	1.41 in. (36 mm)	1.41 in. (36 mm)	2.83 in. (72 mm)	3.15 in. (80 mm)
	3-Pole	2.13 in. (54 mm)	2.13 in. (54 mm)	4.25 in. (108 mm)	4.72 in. (120 mm)