

Set - Screw Rigid Connectors & Couplings

For Threadless Rigid Conduit & IMC

Type 28

Use:

To connect threadless rigid conduit to boxes and enclosures.

Features:

- Concretetight.
- Available with insulated throat.
- Male hub thread (NPS)

Material/Finish:


Malleable Iron/Zinc Plated

Optional Finish:

½" - 1½" Mechanically Galvanized
2" - 6" Hot Dip Galvanized

Contact your local representative for pricing and availability.

Third Party Certification:




Applicable Third Party Standards:

UL Standard: 514B


Fed. Spec./CID: A-A-50553

ANSI/NEMA: FB-1

Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches		
			Body Length	Max Dia.	Thread Length
½	28-050	28-050T	31/32	1¼	7/16
¾	28-075	28-075T	17/16	17/16	7/16
1	28-100	28-100T	17/16	1¾	17/32
1¼	28-125	28-125T	17/16	27/8	5/8
1½	28-150	28-150T	1¾	27/8	5/8
2	28-200	28-200T	17/8	27/8	5/8
2½	28-250	28-250T	27/8	37/16	1
3	28-300	28-300T	27/8	4¼	1
3½	28-350	28-350T	2¾	4¼	17/8
4	28-400	28-400T	3	5¼	17/8
5	28-500	28-500T	4	6¼	1¾
6	28-600	28-600T	4½	77/8	1¾



Type 28-050 — Type 28-200



Type 28-250 — Type 28-600

Type 29

Use:

To couple sections of threadless rigid conduit together.

Features:

Concretetight

Material/Finish:


Malleable Iron/Zinc Plated

Optional Finish:

½" - 1½" Mechanically Galvanized
2" - 6" Hot Dip Galvanized

Contact your local representative for pricing and availability.

Third Party Certification:




Applicable Third Party Standards:

UL Standard: 514B


Fed. Spec./CID: A-A-50553

ANSI/NEMA: FB-1

Trade Size (inches)	Catalog Number	Dimensions in Inches	
		Length	Max. Dia.
½	29-050	1¾	1¾
¾	29-075	27/8	17/16
1	29-100	25/8	1¾
1¼	29-125	2¾	27/8
1½	29-150	37/8	27/8
2	29-200	37/8	27/8
2½	29-250	37/8	37/16
3	29-300	47/8	47/32
3½	29-350	5	4¾
4	29-400	5½	5¼
5	29-500	7½	6¼
6	29-600	8½	77/8



Type 29-050 — Type 29-200



Type 29-250 — Type 29-600