

Specifications for Vinyl Electrical Tapes

	Product Name	Product Description	Tape Thickness	U.V. Resistance	Temp. Rating	Typical Applications	Specs./ Certifications and Listings	U.S. Made
	Scotch® Super 33+™ Professional Use Premium Vinyl Electrical Tape, black	Highly conformable, super stretchy in all weather applications; resists UV rays, abrasion, corrosion.	7 mil	Exceeds UL510 requirements	221°F 105°C	Primary insulation for splices up to 600V. Protective jacketing.	A-A-55809 ASTM D-3005 Type I   RoHS	
	Scotch® Professional Use Vinyl Electrical Tape 35 for Color Coding	Nine fade-resistant colors, super stretchy and conformable, excellent insulating properties. Resists UV rays, abrasion, corrosion, alkalis and acid.	7 mil	Exceeds UL510 requirements	221°F 105°C	Phase identification and marking. Harnessing.	A-A-55809   RoHS	
	Scotch® Professional Use Premium Vinyl Electrical Tape Super 88, black	All weather; heavy duty, professional use, abrasion resistant, fast buildup.	8.5 mil	Exceeds UL510 requirements	221°F 105°C	Primary insulation for splices up to 600V. Protective jacketing.	ASTM D-3005 Type II   RoHS	
	Scotch® Heavy Duty Vinyl Electrical Tape 22, black	Thicker for increased mechanical strength and abrasion resistance. Electrical insulating.	10 mil	Exceeds UL510 requirements	176°F 80°C	Bus bar insulation. Cable jacket repair.	ASTM D-2301 Type II   RoHS	
	Scotch® Vinyl Electrical Tape 66R, black	Excellent mechanical strength, abrasion resistance and electrical insulating properties.	10 mil UL510	Exceeds 105°C requirements	221°F for 600V bus bar	Primary insulation. Protective jacketing.	 RoHS	
	3M™ Highland™ Commercial Grade Electrical Tape, black	Flexible, stretchy, conformable, commercial grade vinyl. Flame retardant.	7 mil	Meets UL510 requirements	194°F 90°C	Protective jacketing. Harnessing. Bundling.	ASTM D-2301 Type I   RoHS	
	3M™ Temflex™ General Purpose Vinyl Electrical Tape 1700, black	Economical, flexible, general purpose tape.	7 mil	Meets UL510 requirements	176°F 80°C	Protective jacketing. Harnessing. Bundling.	ASTM D-2301 Type I   RoHS	No
	3M™ Electrical Tape Training Kit	Supplies Include: Scotch® Super 33+, Scotch Super 88, Scotch Tape 35, Scotch 2200, Scotch 2228, Scotch Tape 70, Scotch Glass 27, Scotch 2520 and Scotch 130C. Other supplies include: split bolt, motor lead, inline splice, bus bar.	N/A	N/A	N/A	N/A	N/A	N/A

Ordering Information for Vinyl Electrical Tapes

Product Name	UPC (054007-)	Size	Inner Unit Pack	Case Qty.
Scotch® Heavy-Duty Vinyl Electrical Tape 22, black				
22	10026	1/2" x 36 yd. (13 mm x 32,9 m)	N/A	48 rolls
22	10034	3/4" x 36 yd. (19 mm x 32,9 m)	1/box 12/ctn	48 rolls
22	10042	1" x 36 yd. (25,4 mm x 32,9 m)	N/A	48 rolls
22	10059	1-1/2" x 36 yd. (38 mm x 32,9 m)	N/A	12 rolls
22	10067	2" x 36 yd. (51 mm x 32,9 m)	N/A	12 rolls
Scotch® Vinyl Electrical Tape 66R, black				
(made to order)		Common Sizes:		
	43249	3/4" x 36 yd. (19 mm x 32,9 m)	N/A	48 rolls
	43250	1" x 36 yd. (25,4 mm x 32,9 m)	N/A	36 rolls
Other sizes available upon request.				
3M® Highland™ Vinyl Electrical Tape	16720	3/4" x 66' (19 mm x 20,1 m)	1/cello	100 rolls
3M® Temflex™ Vinyl Electrical Tape 1700, black				
1700	49700	3/4" x 36 yd. (19 mm x 32,9 m)	1/cello, 10/sleeve	100 rolls
1700	69764	3/4" x 60' (19 mm x 18,3 m)	1/cello, 10/sleeve	100 rolls
1700	49571	3/4" x 66' (19 mm x 20,1 m)	1/cello, 10/sleeve	100 rolls
1700	43962	1" x 66' (25,4 mm x 20,1 m)	N/A	99 rolls
1700P MHSA Printed	08175	3/4" x 66' (19 mm x 20,1 m) [Bulk]	N/A	100 rolls
1700P MHSA Printed	08408	1-1/2" x 44' (38 mm x 13,4 m) [Bulk]	N/A	100 rolls
1700P MHSA Printed	50750	1-1/2" x 66' (38 mm x 20,1 m)	5 rolls/sleeve	100 rolls

Note: Other widths and lengths available upon request.

*Minimum order quantities apply.

**UPC prefix 051131-

PRODUCT REFERRAL GENERATOR

Padding	pg. 14
Moisture Sealing	pg. 14
Splicing	pg. 311
Connecting	
– Lugs and Connectors	pg. 147